

125 Multi-Seal[®]

ROOFING • GUTTERS • CONCRETE • CONSTRUCTION

Colors:

White - 12501
Black - 12502
Grey - 12503
Limestone - 12507
Alum/Grey - 12513
Hunter Green - 12514
Medium Bronze - 12515
Off White - 12516
Redwood Tan - 12517
Stone - 12518
Tan - 12519
Special Bronze - 12520
Brown - 12521
Translucent - 12522

1 Gallon pail

Grey - 12573



- Plastic cartridge
- One year shelf life
- Applies the same in all seasons
- Bonds to wet, damp surfaces
- Long lasting, flexible adhesive
- Many colors available
- Paintable in under an hour*
- Qualifies for LEED Credits
- VOC compliant
- Bonds to Kynar[®] 500

Kynar[®] 500 is a trademark of Arkema Inc.
*Translucent is not paintable

THE IDEAL SEALANT/ADHESIVE FOR:

- | | | |
|--------------|-------------------|-------------------------|
| • Roofing | • Concrete | • Facade & metal |
| • Flashing | • Curbs | clapping joints |
| • Vents | • Wood | • Masonry joints |
| • Downspouts | • Pinhole repairs | • Exterior mastic |
| • Gutters | • Window & door | • Aluminum angle joints |
| • Tiles | perimeter joints | • And more... |

Visit Our Website for Other
BOSS[®] MADE TO WORK Products
www.bossproducts.com

BOSS[®] 400 Colors Window & Siding Sealant
BOSS[®] 399 Neutral Cure Silicone Glazing Sealant
BOSS[®] 334 Genius Gun Minimal Expanding Foam
BOSS[®] 334 Gun Grade Minimal Expanding Foam
BOSS[®] 334 Straw Grade Minimal Expanding Foam



Call The **BOSS[®]** 800-928-BOSS

Soudal Accumetric

350 Ring Road • Elizabethtown • KY 42701

(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412

125 Multi-Seal[®]

ROOFING • GUTTERS • CONCRETE • CONSTRUCTION**TYPICAL PROPERTIES**

	Colors	Translucent
Uncured		
Flow Sag or Slump	NIL	NIL
Tack Free Time	20 min.....	20 min.....
Extrusion Rate	400 g/min.	300 g/min.....
Cured – Physical		
7 Days at 77°F (25°C) and 50% RH (1/8" thickness)		
Durometer Shore A Hardness	35 points.....	17 points.....
Specific Gravity	1.53.....	1.01.....
Tensile Strength	180 psi.....	180.....
Elongation	350%	480%
Modulus.....	130 psi.....	50 psi.....
Shrinkage	NIL	NIL
Service Temperature.....	-40°F to 200°F	
Application Temperature	-35°F to 140°F	

Information on this data sheet is subject to change without notice and should not be used for writing specifications.
For additional information on specific applications, contact Soudal Accumetric.

LIMITATIONS

- Do not use for structural glazing
- It is the sole responsibility of the user to test the adhesion to the substrate for suitability

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN.
OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use with adequate ventilation. Do not handle contact lenses with sealant on hands.
IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The **BOSS[®]** 800-928-BOSS
Soudal Accumetric

350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-BOSS • Fax: (270) 765-2412
www.bossproducts.com

