

CB15 & CB20



Beckett's family of medium condensate pumps are designed to meet or exceed your toughest job demands, including high efficiency gas furnaces. This pump is engineered to be user friendly with features like lift-to-test-tab for the main switch and the ability to mount the pump from either side. It features a larger replaceable Duck-Bill check valve design and convenient discharge with both 3/8" O.D. barb and 1/4" MNPT threads.



| Model # | H | W | L | Outlet | Inlet | Volts | Amps | Watts | Gallons per hour @ 60Hz/ Rated Voltage | | | | Safety Switch | Check Valve | 6 Ft. Cord w/plug | Tubing | 6 Ft. Cord w/plug | Shut Off (Ft.) | Weight Lb. Each |
|-----------|--------|----|---------|-----------|-------|-------|------|-------|---|-----|-----|-----|------------------|----------------|-------------------------|--------|-------------------------|----------------------|-----------------------|
| | | | | | | | | | 1' | 5' | 10' | 15' | | | | | | | |
| CB151UL | 6 1/2" | 5" | 11 1/4" | 3/8" O.D. | 1.1" | 115 | 0.9 | 53 | 125 | 103 | 66 | - | ✓ | ✓ | ✓ | | ✓ | 18' | 3.9 |
| CB151LSUL | 6 1/2" | 5" | 11 1/4" | 3/8" O.D. | 1.1" | 115 | 0.9 | 53 | 125 | 103 | 66 | - | | ✓ | ✓ | | ✓ | 18' | 3.9 |
| CB151TUL | 6 1/2" | 5" | 11 1/4" | 3/8" O.D. | 1.1" | 115 | 0.9 | 53 | 125 | 103 | 66 | - | ✓ | ✓ | ✓ | ✓ | ✓ | 18' | 4.9 |
| CB201UL | 6 1/2" | 5" | 11 1/4" | 3/8" O.D. | 1.1" | 115 | 1.1 | 60 | 115 | 72 | 51 | 20 | ✓ | ✓ | ✓ | | ✓ | 20' | 4.4 |
| CB201LSUL | 6 1/2" | 5" | 11 1/4" | 3/8" O.D. | 1.1" | 115 | 1.1 | 60 | 115 | 72 | 51 | 20 | | ✓ | ✓ | | ✓ | 20' | 4.4 |
| CB201TUL | 6 1/2" | 5" | 11 1/4" | 3/8" O.D. | 1.1" | 115 | 1.1 | 60 | 115 | 72 | 51 | 20 | ✓ | ✓ | ✓ | ✓ | ✓ | 20' | 5.4 |
| CB202TUL | 6 1/2" | 5" | 11 1/4" | 3/8" O.D. | 1.1" | 230 | 1.1 | 89 | 140 | 118 | 84 | 39 | ✓ | ✓ | ✓ | ✓ | ✓ | 20' | 5.4 |
| CB202UL | 6 1/2" | 5" | 11 1/4" | 3/8" O.D. | 1.1" | 230 | 1.1 | 89 | 140 | 118 | 84 | 39 | ✓ | ✓ | ✓ | | ✓ | 20' | 4.4 |

Average Performance

Beckett Automatic Condensate Units Coding Legend:

- 1- 115V 2- 230V
- T- Tubing Included (20 ft. of 3/8 in. I.D.)
- LS- Less Safety Switch
- UL- Standard Unit 150°F Max. Water Temp.

Tank Capacity:

CB15, CB20..... 2.0 US quart (1.9 Liters)