



# A Unique Indoor Unit that Offers Extremely Easy Maintenance

## FEATURES

- Modes: Cool, Heat, Dry, Fan, Auto
- 4-way installation (Up flow, Down flow, Right, Left)
- New aluminum coil
- Automatic Airflow Technology with static pressure up to 0.8 inWG
- Less than 2% air leakage
- Easy maintenance
- Quiet indoor operation
- Anti-corrosive fin coating

## COMPATIBLE WITH:

- 38MBRC Single Zone Outdoor Unit

Performance  
SERIES

Size: 36 / 48 / 60

## KEY FEATURES

### Unmatched Maintenance Simplicity

With a top panel and an indoor coil that can be easily removed, get faster access to the core parts of the unit needed for service. You only need to remove two screws!

### Less Complex Electronics

Having only two integrated printed circuit boards means the electronic components are less complicated. One is the main control board, and the other is the function board for the 24V Interface, dip switch, wired controller and LED display.

### Easier Access to Electric Heater

This single-piece construction enables easy installation and maintenance.

### Modular Slide Design

The indoor coil can be easily pulled out through the slide track for quick and easy maintenance.

## CONTROLS

Wireless Remote Controller included with indoor unit

24V Interface for third party thermostat compatibility built-in

## WARRANTY

Limited Warranty\*

10-year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years.



## SPECIFICATIONS:

40MBAB Air Handler				
Heat Pump				
System				
Size		36	48	60
Indoor Model		40MBABQ36XA3	40MBABQ48XA3	40MBABQ60XA3
Electrical				
Voltage-Phase-Cycle	V-Ph-Hz	208/230-1-60	208/230-1-60	208/230-1-60
Power Supply		Indoor unit powered from outdoor unit		
MCA	A.	5	7.5	9
Controls				
Wireless Remote Controller (° F/° C Convertible)		Standard	Standard	Standard
Wired Remote Controller (° F/° C Convertible)		Standard	Standard	Standard
Operating Range				
Cooling Indoor DB Min - Max	° F (° C)	60~90 (16~32)	60~90 (16~32)	60~90 (16~32)
Heating Indoor DB Min - Max	° F (° C)	32~86 (0~30)	32~86 (0~30)	32~86 (0~30)
Piping				
Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)
Pipe Connection Size - Suction	in (mm)	5/8 (16)	5/8 (16)	7/8 (22)
Indoor				
Unit Width	in (mm)	21 (534)	21 (534)	24.5 (622)
Unit Height	in (mm)	49 (1245)	49 (1245)	53 (1346)
Unit Depth	in (mm)	21 (534)	21 (534)	21 (534)
Net Weight	lbs (kg)	129.63 (58.8)	132.5 (60.1)	164.02 (74.4)
Number of Fan Speeds		4	4	4
Airflow (lowest to highest)	CFM	865/971/1082/1188	906/1094/1282/1471	1135/1359/1582/1806
Sound Pressure - Cooling (lowest to highest)	dB(A)	41.4/44.0/48.5	44.6/47.7/51.0/53.7	45.7/47.5/51.2/53.3
Sound Pressure - Heating (lowest to highest)	dB(A)	33.9/39.0/45.1	43.4/47.8/50.5/53.8	39.4/44.9/50.1/51.0
Max Static Pressure	In.WG.	0.8	0.8	0.8
Field Drain Pipe Size O.D.	in (mm)	3/4 (19.1)	3/4 (19.1)	3/4 (19.1)

\*Performance may vary based on the compatible outdoor units. See respective pages for performance data.

## COMPATIBILITY:

Indoor Unit	40MBABQ36XA3	40MBABQ48XA3	40MBABQ60XA3
Outdoor Unit Single Zone	38MBRCQ36AA3	38MBRCQ48AA3	38MBRCQ58AA3

Manufacturer reserves the right to discontinue, or change at any time, specification or designs without notice or incurring obligations.