



MINI-SPLIT CONDENSATE DRAIN HOSE AND FITTINGS

HOSE STYLES

Smooth Bore
Reduces resistance and maximizes condensate flow. Resists clogging.

Insulated
Protects hose from sweating that can occur from cooler condensate and warmer ambient air.

UV Resistance
Resists deterioration from Sunlight.



NON-INSULATED DRAIN HOSE

RS # (ref. #)

Code	ID	LENGTH	CTN QTY	CTN WT
83001 (DH-14) SMOOTH BORE	1/2 in	164 ft	1	6 lbs.
83012 (DSH-20N) SMOOTH BORE	5/8 in	164 ft	1	7 lbs.
83003 (DH-16S) STANDARD	5/8 in	20 ft	5	6 lbs.
83004 (DHQ-16) UV RESISTANT	5/8 in	164 ft	1	6 lbs.
83005 (DSB-16) SMOOTH BORE	5/8 in	65 ft	1	2 lbs.

INSULATED DRAIN HOSE

Code	ID	LENGTH	CTN QTY	CTN WT
83011 (DSH-14) SMOOTH BORE	1/2 in	65 ft	1	7 lbs.
83012 (DSH-20N) SMOOTH BORE	3/4 in	65 ft	1	10 lbs.
83013 (DSH-25N) SMOOTH BORE	1 in	65 ft	1	13 lbs.

HOSE COUPLER

Code	ID	LENGTH	CTN QTY	CTN WT
83021 (DSH14J) JOIN DSH-14	1/2 in	-	10	1 lb.
83023 (DSH20NJ) JOIN DSH-20	3/4 in	-	10	1 lb.
83028 (DHJ-14)	1/2 in	-	10	1 lb.
83029 (DHJ-16)	5/8 in	-	10	1 lb.
83031 (DSH-14C) INSULATED	-	-	10	2 lbs.

PIPE ADAPTOR

Code	ID	LENGTH	CTN QTY	CTN WT
83020 (DH-14-16V) DSH-14 TO 3/4 PVC	3/4 in	-	10	2 lbs.
83024 (DSH-20-NV) DSH-20 TO 3/4 PVC	3/4 in	-	10	2 lbs.

VENTED DRAIN WYE

Code	ID	LENGTH	CTN QTY	CTN WT
83022 (DY-16)	5/8 in	-	10	1 lbs.

*EZT-180 Mini waterless in-line trap can be found on page 19.

WALL SLEEVE

Code	SIZE	CTN QTY	CTN WT
83017 (NFP-75) WALL SLEEVE	3"x 5" - 7"	10	1 lb.

NON-ADHESIVE WRAP

Code	SIZE	CTN QTY	CTN WT
83016 (HN-75-I) UV RESISTANT NON-ADHESIVE WRAP	3" x 70'	4	1 lb.

INTERCONNECT CABLE

Code	SIZE	CTN QTY	CTN WT
87795 (CAB-14450) 4/C 14 GAUGE SHIELDED	50'	1	5 lbs.
87790 (CAB-144100) 4/C 14 GAUGE SHIELDED	100'	1	10 lbs.