

MAYTAG®

TECHNICAL SPECIFICATIONS

Model CSA3BE Series



M120 Product Line

**High Efficiency Air Conditioner
14.3 / 13.8 SEER2 — 1.5 - 5 Ton Capacity**

The CSA3BE Series of air conditioners offers exceptional performance. The unit, when combined with our engineered coils or air handlers, offers a full line of quality, split system cooling equipment.

Features and Benefits


- **Quality Compressor** – State-of-the-art Copeland Scroll™ compressor is standard equipment.
- **Designed Using Galvanized Steel** – Durable brushed stainless steel protects the coil from yard hazards and extreme weather. Unit is trimmed in a silicone-protected polyester finish that passes 950 hours of salt spray per ASTM Std. B117.
- **Quiet Plus™ Sound Package** – Consists of a Quiet Plus™ Compressor Sound Blanket and a Swept Wing Fan Blade. Both have been engineered to significantly reduce unwanted noise.
- **Permanently Lubricated Motor** – A heavy duty PSC motor for long lasting reliability and quiet operation. Requires no maintenance and is completely protected from rain and snow.
- **Removable Top Grille Assembly** – Allows ease of service from the top without disconnecting fan motor leads.
- **High Pressure Switch** – Protects against abnormally high system pressures. Auto-reset feature prevents nuisance service visits.
- **Liquid Line Filter / Drier** – Included with unit, field installed.
- **One Piece Top/Orifice** – Designed for maximum airflow and quiet operation.
- **Easy Compressor and Control Access** – Designed to make servicing easier for the contractor, access panels are provided to all controls and the compressor from the side of the unit.
- **Composite Base Pan** – Absorbs sound and is corrosion resistant. Composite is also stronger and lighter than steel.
- **All-Aluminum Coils** – All aluminum coils which provides high corrosion resistance.
- **Servicer-Friendly Jacket** – Side panels can be easily removed and replaced without removing the top grill.

DIMENSIONS/OUTDOOR SECTION

14.3 SEER2 — High Efficiency

CSA3BE	18K	24K	30K	36K	42K	48K	60KA
H	29.25	29.25	29.25	41.25	45.25	45.25	45.25
W	31.5	31.5	31.5	31.5	31.5	31.5	31.5
D	31.5	31.5	31.5	31.5	31.5	31.5	31.5

Air Discharge Allow Adequate Clearance for Airflow



IDENTIFICATION CODE

C S A 3 B E 4 M 1 S N 18 K A													Revision
Jacket Style	Split System	A - Air Conditioner H - Heat Pump	Design Series	B - Brazed	D - 13.4 SEER2 E - 14.3 SEER2 F - 15.2 SEER2 G - 18-20 SEER2	Refrigerant 4 - R-410A	M - Micro-Channel C - Copper Coil	Stages 1 - Single 2 - Two V - Inverter	Compressor S - Scroll R - Rotary	Metering Device N - None X - TXV P - Piston E - EXV	Size (MBTU)	Voltages K - 208/230-1-60	

PHYSICAL AND ELECTRICAL SPECIFICATIONS/OUTDOOR UNITS

14.3 SEER2 — High Efficiency

Model Number CSA3BE			18K	24K	30K	36K	42K	48K	60KA
Electrical Data	Volts-Cycles-Phase (1)		208/230-60-1						
	Delay Fuse Max. (2)		20	25	25	30	40	45	50
	Min. Circuit Ampacity		12.1	15.4	16.9	18.6	23.5	26.2	29.9
Component Data	Fan Motor	HP	1/8	1/8	1/8	1/5	1/4	1/4	1/4
	Compressor Data	LRA	42.6	61.0	65.0	87.4	110.2	110.0	147.4
Refrigerant suction line O.D. NOTE: Liquid line is 3/8" O.D. for entire length."		0-24 ft.	3/4"	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"
		25-39 ft.	3/4"	3/4"	3/4"	7/8" (3)	7/8"	7/8"	1-1/8" (4)
		40-75 ft.	3/4"	3/4"	3/4"	7/8" (3)	7/8"	7/8"	1-1/8" (4)
Approximate Shipping Weight (lbs.)			187	192	197	225	273	264	250
Sound Rating db			69	69	69	71	73	74	75

(1) Operating Voltage Range: 187v min. — 253v max.

(2) HACR Type Circuit Breakers may be used.

(3) Requires 7/8" to 3/4" reducer from line to unit.

(4) Requires 7/8" to 1-1/8" reducer from line to unit.

ACCESSORIES - CONDENSING UNIT

Start Assist Kit - 912933

Provides additional starting torque for the compressor motor when operating with low line voltage or high operating temperatures.

High Wind Tie-Down Kits - <http://miamitech.com/products/metal/cutdnortek.html>

Low Ambient Kit - 918837

Cantilever Mounting Kit - 1018671

Four mounting corner post/panel split system design to cantilever mounts.

SYSTEM COOLING CAPACITIES - HIGH EFFICIENCY - SINGLE PHASE

Outdoor Unit	Indoor Unit	BTUH	SEER2	EER2	CFM
CSA3BE4M1SN18K	C74B(A,H)MX24C-A	18,000	14.3	11.7	605
CSA3BE4M1SN18K	C74B(A,H)MX24C-B	18,000	14.3	11.7	605
CSA3BE4M1SN24K	C74B(A,H)MX24C-A	23,600	14.3	11.7	805
CSA3BE4M1SN24K	C74B(A,H)MX24C-B	23,600	14.3	11.7	805
CSA3BE4M1SN30K	C74B(A,H)MX30C-A	28,600	14.3	11.7	1,010
CSA3BE4M1SN30K	C74B(A,H)MX30C-B	28,600	14.3	11.7	1,010
CSA3BE4M1SN30K	C74B(A,H)MX30C-C	28,600	14.3	11.7	1,010
CSA3BE4M1SN36K	C74B(A,H)MX36C-B	34,800	14.3	11.7	1,195
CSA3BE4M1SN36K	C74B(A,H)MX36C-C	34,800	14.3	11.7	1,195
CSA3BE4M1SN42K	C74B(A,H)MX42C-C	40,500	14.3	11.7	1,410
CSA3BE4M1SN42K	C74B(A,H)MX42C-D	40,500	14.3	11.7	1,410
CSA3BE4M1SN48K	C74B(A,H)MX48C-C	45,000	13.8	11.2	1,600
CSA3BE4M1SN48K	C74B(A,H)MX48C-D	45,000	13.8	11.2	1,600
CSA3BE4M2SN60KA	C74B(A,H)MX60C-C	56,000	13.8	11.2	1,530
CSA3BE4M2SN60KA	C74B(A,H)MX60C-D	56,000	13.8	11.2	1,530

See current AHRI Directory for certified combinations and ratings. All ratings are with time delay relay.
www.ahridirectory.org

COOLING EXPANDED RATINGS WITH COIL

CSA3BE4M1SN18K + C74B(A,H)MX24C-A

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
525	80	62	18.9	15.6	1.06	18.1	15.3	1.14	17.2	14.9	1.26	16.4	14.5	1.40	15.4	14.0	1.55	14.1	13.5	1.70
	80	67	20.7	13.3	1.02	19.7	12.8	1.12	19.2	12.6	1.21	18.0	12.1	1.40	17.0	11.7	1.55	15.6	11.1	1.69
	80	72	22.4	10.7	1.00	21.4	10.3	1.11	20.4	9.9	1.23	19.7	9.6	1.37	18.6	9.2	1.52	17.1	8.7	1.69
	75	62	18.9	13.3	1.06	18.0	12.9	1.14	17.2	12.5	1.26	16.3	12.2	1.40	15.3	11.6	1.55	14.1	11.0	1.70
	75	67	20.6	10.9	1.02	19.7	10.5	1.13	18.9	10.2	1.25	18.0	9.7	1.40	16.8	9.2	1.55	15.5	8.7	1.69
600	80	62	19.4	16.6	1.09	18.5	16.3	1.17	17.6	15.7	1.29	16.7	15.6	1.43	15.7	15.1	1.58	14.4	14.3	1.73
	80	67	21.2	13.9	1.05	20.2	13.5	1.15	19.6	13.2	1.24	18.4	12.7	1.43	17.3	12.3	1.58	15.9	11.7	1.73
	80	72	22.9	11.1	1.03	21.8	10.7	1.14	20.7	10.3	1.26	20.0	10.0	1.40	18.9	9.6	1.55	17.4	9.0	1.72
	75	62	19.4	14.1	1.09	18.5	13.6	1.17	17.6	13.2	1.29	16.6	12.8	1.43	15.6	12.3	1.58	14.3	11.7	1.73
	75	67	21.1	11.3	1.05	20.1	10.9	1.16	19.2	10.5	1.28	18.3	10.1	1.43	17.2	9.6	1.58	15.8	9.0	1.72
675	80	62	19.8	17.5	1.12	18.8	17.2	1.20	17.9	16.9	1.32	17.0	16.4	1.46	15.9	15.8	1.61	14.8	14.8	1.76
	80	67	21.6	14.6	1.08	20.6	14.2	1.19	19.9	13.9	1.27	18.7	13.3	1.46	17.6	12.9	1.61	16.1	12.3	1.76
	80	72	23.2	11.5	1.06	22.2	11.1	1.17	21.1	10.6	1.29	20.3	10.3	1.43	19.2	9.9	1.59	17.6	9.3	1.75
	75	62	19.7	14.8	1.12	18.8	14.2	1.20	17.8	13.9	1.32	16.9	13.5	1.46	15.9	12.9	1.61	14.5	12.3	1.76
	75	67	21.5	11.7	1.08	20.5	11.3	1.19	19.6	10.9	1.31	18.6	10.5	1.46	17.4	10.0	1.61	16.0	9.3	1.76

CSA3BE4M1SN24K + C74B(A,H)MX24C-A

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
700	80	62	25.1	20.8	1.38	24.0	20.3	1.51	22.8	19.7	1.67	21.8	19.2	1.86	20.5	18.7	2.06	18.9	18.0	2.28
	80	67	27.2	17.5	1.36	26.0	16.9	1.50	25.3	16.6	1.61	23.9	16.0	1.85	22.6	15.4	2.06	20.9	14.6	2.27
	80	72	29.2	14.1	1.35	28.0	13.5	1.48	27.0	13.1	1.65	26.0	12.7	1.84	24.5	12.2	2.04	22.6	11.4	2.26
	75	62	25.0	17.6	1.38	23.9	17.2	1.51	22.8	16.7	1.67	21.7	16.0	1.86	20.5	15.4	2.06	18.9	14.6	2.27
	75	67	27.2	14.4	1.36	26.0	13.9	1.50	24.9	13.4	1.66	23.6	12.8	1.85	22.5	12.3	2.06	20.8	11.6	2.27
800	80	62	25.7	22.0	1.42	24.5	21.6	1.55	23.3	21.1	1.71	22.2	20.6	1.90	20.9	20.0	2.10	19.2	18.8	2.32
	80	67	27.8	18.3	1.40	26.6	17.8	1.54	25.8	17.5	1.65	24.4	16.9	1.90	23.0	16.2	2.10	21.0	15.3	2.32
	80	72	29.9	14.6	1.39	28.6	14.1	1.53	27.5	13.6	1.69	26.4	13.2	1.88	25.0	12.6	2.09	22.9	11.8	2.31
	75	62	25.6	18.6	1.43	24.4	18.1	1.55	23.3	17.5	1.71	22.1	16.9	1.90	20.8	16.3	2.10	19.2	15.4	2.32
	75	67	27.8	14.9	1.40	26.5	14.4	1.54	25.4	13.9	1.71	24.1	13.3	1.89	22.9	12.8	2.10	21.0	12.0	2.32
900	80	62	26.1	23.2	1.47	24.9	22.8	1.59	23.6	22.3	1.75	22.5	21.7	1.94	21.2	21.0	2.15	19.7	19.7	2.36
	80	67	28.3	19.1	1.45	27.0	18.6	1.58	26.3	18.3	1.70	24.7	17.6	1.94	23.3	17.0	2.14	21.2	16.0	2.36
	80	72	30.3	15.0	1.43	29.2	14.5	1.57	27.9	14.0	1.73	26.7	13.6	1.92	25.3	13.0	2.13	23.1	12.3	2.35
	75	62	26.0	19.4	1.47	24.8	18.9	1.60	23.6	18.4	1.75	22.4	17.7	1.94	21.1	17.1	2.14	19.4	16.1	2.36
	75	67	28.2	15.4	1.45	27.0	14.9	1.58	25.8	14.4	1.75	24.4	13.7	1.94	23.2	13.2	2.14	21.3	12.3	2.36

CSA3BE4M1SN30K + C74B(A,H)MX30C-A

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
875	80	62	29.8	25.1	1.66	28.2	24.4	1.80	26.9	23.7	1.97	25.6	23.2	2.17	24.0	22.6	2.39	22.1	21.5	2.64
	80	67	32.1	20.9	1.64	30.6	20.2	1.79	29.8	19.9	1.92	28.3	19.2	2.18	26.6	18.5	2.40	24.4	17.6	2.64
	80	72	34.7	16.8	1.63	33.3	16.2	1.79	31.8	15.7	1.97	30.3	15.1	2.17	28.6	14.4	2.39	26.7	13.6	2.64
	75	62	29.7	21.3	1.66	28.1	20.6	1.80	26.8	19.9	1.97	25.6	19.3	2.17	24.0	18.4	2.39	22.2	17.6	2.63
	75	67	32.0	17.1	1.64	30.5	16.4	1.80	29.3	15.9	1.97	28.1	15.4	2.18	26.5	14.7	2.40	24.3	13.8	2.64
1000	80	62	30.4	26.7	1.71	28.7	25.9	1.86	27.4	25.4	2.03	26.0	24.8	2.23	24.4	23.8	2.45	22.7	22.7	2.70
	80	67	32.8	21.9	1.69	31.2	21.3	1.85	30.3	20.9	1.97	28.7	20.3	2.24	27.0	19.4	2.46	24.7	18.5	2.70
	80	72	35.4	17.5	1.69	34.0	16.9	1.85	32.4	16.2	2.02	30.9	15.6	2.22	29.1	14.9	2.45	27.1	14.2	2.70
	75	62	30.3	22.4	1.71	28.7	21.7	1.86	27.3	21.0	2.03	26.0	20.4	2.23	24.4	19.4	2.45	22.5	18.5	2.69
	75	67	32.7	17.7	1.70	31.1	17.1	1.85	29.9	16.6	2.03	28.6	16.0	2.23	26.9	15.3	2.46	24.7	14.2	2.69
1125	80	62	31.0	28.1	1.77	29.2	27.5	1.91	27.7	26.8	2.09	26.4	25.9	2.28	25.0	25.0	2.51	23.2	23.3	2.75
	80	67	33.3	22.9	1.75	31.6	22.2	1.91	30.8	21.8	2.03	29.1	21.2	2.29	27.3	20.4	2.51	25.0	19.5	2.75
	80	72	35.9	17.9	1.75	34.4	17.3	1.91	32.8	16.7	2.08	31.3	16.2	2.28	29.4	15.5	2.50	27.3	14.7	2.76
	75	62	30.8	23.5	1.77	29.1	22.7	1.91	27.6	22.0	2.09	26.3	21.4	2.28	24.7	20.5	2.50	22.7	19.5	2.75
	75	67	33.2	18.3	1.75	31.5	17.6	1.91	30.3	17.1	2.09	29.0	16.5	2.29	27.0	15.7	2.51	24.9	14.8	2.75

COOLING EXPANDED RATINGS WITH COIL (CONTINUED)

CSA3BE4M1SN36K + C74B(A,H)MX36C-B

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1050	80	62	36.9	31.4	1.96	35.1	30.7	2.18	33.5	29.7	2.40	31.9	29.2	2.65	30.0	28.3	2.91	27.5	27.0	3.19
	80	67	39.8	26.1	1.93	38.2	25.4	2.17	37.1	24.9	2.34	35.0	23.9	2.66	33.1	23.2	2.92	30.5	22.1	3.20
	80	72	42.8	20.9	1.91	41.2	20.2	2.16	39.5	19.6	2.40	37.9	19.0	2.66	35.9	18.3	2.93	33.0	17.0	3.21
	75	62	36.8	26.6	1.96	35.0	25.9	2.18	33.4	25.1	2.40	31.8	24.2	2.64	30.1	23.1	2.90	27.8	22.1	3.18
	75	67	39.8	21.5	1.94	38.1	20.7	2.17	36.5	20.0	2.41	34.9	19.3	2.66	32.9	18.4	2.91	30.4	17.4	3.20
1200	80	62	37.3	33.0	2.10	35.5	32.3	2.33	33.8	31.7	2.56	32.1	30.9	2.80	30.2	29.7	3.06	28.0	28.0	3.35
	80	67	40.3	27.1	2.08	38.7	26.5	2.32	37.5	25.8	2.49	35.3	25.2	2.81	33.3	24.0	3.08	30.6	22.9	3.35
	80	72	43.4	21.4	2.06	41.7	20.8	2.31	40.0	20.2	2.55	38.2	19.4	2.81	36.1	18.5	3.08	33.1	17.4	3.37
	75	62	37.2	27.8	2.11	35.4	27.0	2.33	33.7	26.2	2.56	32.1	25.4	2.80	30.2	24.1	3.06	27.9	23.0	3.33
	75	67	40.3	21.9	2.09	38.5	21.1	2.32	36.9	20.5	2.56	35.2	19.8	2.81	33.2	18.9	3.07	30.4	17.7	3.35
1350	80	62	37.6	33.9	2.25	35.7	34.1	2.48	34.0	33.2	2.71	32.4	32.1	2.95	30.7	30.7	3.22	28.4	28.4	3.50
	80	67	40.7	28.1	2.23	38.9	27.5	2.47	37.8	26.8	2.64	35.5	26.1	2.97	33.4	24.9	3.23	30.6	23.9	3.51
	80	72	43.6	21.8	2.21	42.0	21.1	2.46	40.1	20.4	2.70	38.4	19.8	2.96	36.2	19.0	3.23	33.1	17.8	3.52
	75	62	37.5	28.8	2.26	35.6	28.1	2.48	33.9	27.3	2.71	32.2	26.5	2.95	30.3	24.9	3.21	27.9	23.8	3.48
	75	67	40.6	22.4	2.24	38.8	21.6	2.47	37.1	21.0	2.71	35.3	20.1	2.96	33.2	19.2	3.22	30.4	18.0	3.50

CSA3BE4M1SN42K + C74B(A,H)MX42C-C

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1225	80	62	41.4	34.5	2.43	40.2	34.0	2.64	38.8	33.2	2.89	37.0	32.4	3.19	35.0	31.4	3.53	32.9	30.4	3.92
	80	67	45.2	29.2	2.43	43.7	28.6	2.64	42.6	28.1	2.81	40.3	27.1	3.15	38.3	26.2	3.46	36.2	25.3	3.84
	80	72	50.1	24.2	2.44	48.4	23.5	2.66	46.4	22.7	2.89	44.3	21.9	3.16	42.0	21.0	3.46	39.6	20.0	3.82
	75	62	41.3	29.4	2.43	40.0	28.8	2.64	38.6	28.0	2.89	36.9	27.3	3.19	34.8	26.3	3.55	32.8	25.3	3.92
	75	67	45.1	24.1	2.43	43.5	23.4	2.64	42.0	22.7	2.88	40.2	21.9	3.15	38.2	21.1	3.46	36.1	20.2	3.84
1410	80	62	42.5	36.8	2.46	41.2	36.2	2.67	39.7	35.4	2.92	37.9	34.5	3.22	35.9	33.6	3.56	33.6	32.5	3.94
	80	67	46.4	31.0	2.46	44.8	30.3	2.67	43.7	29.8	2.84	41.3	28.7	3.18	39.2	27.8	3.49	37.0	26.9	3.87
	80	72	51.4	25.3	2.47	49.6	24.7	2.69	47.5	23.8	2.92	45.2	22.9	3.19	42.9	22.0	3.50	40.4	21.1	3.85
	75	62	42.4	31.1	2.46	41.0	30.4	2.67	39.6	29.7	2.92	37.8	28.9	3.22	35.7	27.9	3.56	33.5	26.8	3.94
	75	67	46.2	25.2	2.46	44.6	24.5	2.67	43.0	23.8	2.91	41.1	23.0	3.18	39.1	22.1	3.49	36.8	21.1	3.87
1575	80	62	43.3	38.7	2.49	41.9	38.1	2.70	40.4	37.2	2.95	38.6	36.5	3.24	36.4	35.4	3.58	34.2	34.1	3.97
	80	67	47.3	32.4	2.49	45.6	31.6	2.70	44.4	31.1	2.86	41.9	30.1	3.21	39.8	29.2	3.52	37.5	28.2	3.90
	80	72	52.3	26.2	2.50	50.5	25.5	2.71	48.4	24.7	2.95	46.0	23.8	3.22	43.5	22.9	3.52	41.0	21.9	3.88
	75	62	43.2	32.6	2.49	41.8	31.8	2.70	40.3	31.2	2.95	38.4	30.2	3.24	36.3	29.2	3.58	34.0	28.2	3.97
	75	67	47.1	26.2	2.49	45.4	25.4	2.70	43.7	24.7	2.94	41.8	23.8	3.21	39.7	22.9	3.52	37.4	22.0	3.90

CSA3BE4M1SN48K + C74B(A,H)MX48C-C

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1400	80	62	46.5	38.3	2.81	45.2	37.7	3.05	43.6	36.9	3.33	41.7	36.0	3.66	39.7	34.9	4.05	37.4	33.7	4.51
	80	67	50.8	32.4	2.81	49.2	31.7	3.05	47.9	31.2	3.24	45.3	30.0	3.66	43.1	29.0	4.03	40.9	28.0	4.47
	80	72	56.3	26.7	2.83	54.3	25.9	3.06	52.0	25.0	3.34	49.6	24.1	3.67	47.2	23.0	4.05	44.5	22.0	4.48
	75	62	46.4	32.7	2.81	45.1	32.0	3.05	43.5	31.2	3.33	41.6	30.3	3.66	39.5	29.3	4.05	37.3	28.2	4.51
	75	67	50.6	26.6	2.81	49.0	25.8	3.05	47.2	25.1	3.33	45.2	24.3	3.65	43.0	23.3	4.03	40.7	22.3	4.47
1600	80	62	47.5	40.4	2.90	46.1	39.8	3.14	44.4	38.9	3.42	42.5	37.9	3.75	40.3	37.0	4.14	38.0	35.8	4.60
	80	67	51.9	33.9	2.90	50.1	33.2	3.14	48.8	32.6	3.33	46.1	31.4	3.75	43.8	30.4	4.12	41.5	29.4	4.56
	80	72	57.5	27.7	2.92	55.4	26.8	3.15	53.0	25.8	3.44	50.5	24.8	3.76	47.8	23.9	4.14	45.2	22.9	4.57
	75	62	47.5	34.2	2.90	46.0	33.6	3.14	44.3	32.7	3.42	42.4	31.7	3.75	40.2	30.7	4.14	37.8	29.5	4.60
	75	67	51.6	27.5	2.90	50.0	26.8	3.14	48.0	26.0	3.42	45.9	25.0	3.75	43.7	24.0	4.12	41.3	23.0	4.56
1800	80	62	48.2	42.3	2.99	46.8	41.6	3.23	45.0	41.0	3.51	43.1	40.1	3.84	40.8	38.9	4.23	38.4	37.7	4.68
	80	67	52.6	35.3	2.99	50.9	34.6	3.23	49.5	34.0	3.42	46.7	32.8	3.84	44.3	31.8	4.22	41.9	30.7	4.65
	80	72	58.5	28.4	3.00	56.1	27.5	3.24	53.7	26.6	3.53	51.1	25.7	3.85	48.4	24.6	4.23	45.6	23.5	4.66
	75	62	48.0	35.6	2.99	46.6	34.9	3.23	44.9	34.0	3.51	42.9	33.1	3.84	40.7	32.0	4.23	38.2	30.8	4.68
	75	67	52.4	28.3	2.99	50.7	27.5	3.23	48.7	26.7	3.51	46.5	25.8	3.84	44.2	24.8	4.21	41.7	23.8	4.65

COOLING EXPANDED RATINGS WITH COIL (CONTINUED)

CSA3BE4M2SN60KA + C74B(A,H)MX60C-C High Speed

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1530	80	62	57.9	47.2	3.69	56.2	46.4	4.02	54.2	45.4	4.39	51.8	44.2	4.83	49.1	42.8	5.31	46.1	41.3	5.84
	80	67	62.9	40.0	3.73	60.9	39.1	4.05	58.7	38.2	4.41	56.2	37.0	4.82	53.3	35.7	5.28	50.3	34.4	5.80
	80	72	69.5	33.2	3.80	67.0	32.2	4.11	64.4	31.1	4.47	61.2	29.8	4.87	57.9	28.5	5.33	54.7	27.3	5.83
	75	62	57.7	40.4	3.69	56.1	39.6	4.01	54.1	38.6	4.39	51.7	37.4	4.83	49.0	36.1	5.30	46.0	34.6	5.83
	75	67	62.7	33.1	3.73	60.7	32.2	4.05	58.5	31.2	4.41	56.1	30.2	4.82	53.3	28.9	5.28	50.1	27.5	5.80
1875	80	62	59.7	51.3	3.86	58.0	50.2	4.19	55.8	49.2	4.56	53.3	48.5	4.99	50.5	47.3	5.46	47.4	45.6	5.98
	80	67	64.9	43.0	3.90	62.8	42.2	4.22	60.4	41.2	4.58	57.6	40.0	4.99	54.7	38.6	5.45	51.5	37.2	5.97
	80	72	71.8	35.0	3.97	69.1	34.0	4.28	66.1	32.9	4.64	62.8	31.6	5.04	59.3	30.1	5.50	55.8	28.8	6.00
	75	62	59.5	43.3	3.86	57.8	42.6	4.19	55.7	41.6	4.56	53.2	40.4	4.99	50.3	39.0	5.46	47.2	37.5	5.98
	75	67	64.7	34.9	3.90	62.6	34.0	4.22	60.1	33.0	4.58	57.4	31.8	4.99	54.4	30.6	5.45	51.3	29.2	5.97
2000	80	62	60.2	52.4	3.93	58.4	51.7	4.25	56.3	51.3	4.62	53.7	50.1	5.05	50.8	48.6	5.51	47.7	46.7	6.04
	80	67	65.4	44.0	3.97	63.3	43.2	4.28	60.8	42.2	4.64	58.0	40.9	5.05	55.0	39.6	5.51	51.8	38.2	6.03
	80	72	72.4	35.7	4.04	69.6	34.6	4.35	66.5	33.4	4.70	62.7	31.9	5.10	59.6	30.7	5.56	56.1	29.4	6.06
	75	62	60.1	44.5	3.92	58.3	43.6	4.25	56.1	42.6	4.62	53.5	41.2	5.05	50.7	40.1	5.52	47.4	38.5	6.04
	75	67	65.2	35.6	3.96	63.1	34.7	4.28	60.6	33.6	4.64	57.8	32.4	5.05	54.8	31.2	5.51	51.6	29.7	6.03

CSA3BE4M2SN60KA + C74B(A,H)MX60C-C Low Speed

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1145	80	62	42.5	35.0	2.55	41.1	34.4	2.86	39.2	33.3	3.21	36.9	32.1	3.60	34.4	31.1	4.04	31.4	29.8	4.54
	80	67	46.7	29.9	2.53	45.0	29.1	2.85	42.9	28.2	3.19	40.5	27.1	3.58	37.8	25.9	4.01	34.9	24.7	4.49
	80	72	51.8	24.8	2.54	49.7	23.9	2.85	47.3	22.9	3.20	44.6	21.8	3.58	41.6	20.7	4.00	38.6	19.5	4.48
	75	62	42.5	29.9	2.55	41.0	29.2	2.87	39.1	28.3	3.21	36.8	27.2	3.60	34.2	25.9	4.04	31.3	24.5	4.55
	75	67	46.5	24.6	2.53	44.8	23.8	2.85	42.7	22.9	3.20	40.3	21.8	3.58	37.7	20.7	4.01	34.8	19.5	4.49
1405	80	62	44.1	38.6	2.65	42.5	37.6	2.97	40.5	36.9	3.32	38.1	35.9	3.71	35.3	34.4	4.15	32.7	32.7	4.65
	80	67	48.4	32.3	2.64	46.5	31.5	2.96	44.2	30.4	3.31	41.7	29.4	3.69	38.9	28.0	4.12	35.9	26.8	4.61
	80	72	53.7	26.2	2.64	51.5	25.4	2.96	48.8	24.3	3.31	45.9	23.1	3.69	42.7	21.9	4.12	39.6	20.8	4.59
	75	62	43.9	32.2	2.66	42.4	31.5	2.97	40.4	30.6	3.32	38.0	29.3	3.71	35.2	28.0	4.15	32.2	26.5	4.66
	75	67	48.1	26.0	2.64	46.3	25.3	2.96	44.1	24.3	3.31	41.5	23.3	3.69	38.7	22.1	4.12	35.7	20.7	4.61
1500	80	62	44.5	39.6	2.69	42.9	38.9	3.01	40.8	38.1	3.36	38.4	37.0	3.75	35.7	35.4	4.19	33.2	33.2	4.69
	80	67	48.8	33.0	2.68	46.9	32.2	3.00	44.6	31.1	3.35	42.0	30.1	3.73	39.1	28.7	4.16	36.1	27.4	4.65
	80	72	54.3	26.8	2.68	51.9	25.8	3.00	49.3	24.8	3.35	46.3	23.6	3.73	43.1	22.4	4.16	39.9	21.2	4.63
	75	62	44.4	33.0	2.69	42.8	32.2	3.02	40.7	31.2	3.36	38.3	30.1	3.75	35.5	28.8	4.19	32.4	27.5	4.70
	75	67	48.6	26.6	2.68	46.8	25.8	3.00	44.5	24.8	3.35	41.9	23.7	3.73	39.0	22.4	4.16	35.9	21.2	4.65



MAYTAG

Before purchasing this appliance, read important energy cost and efficiency information available from your retailer. Specifications and illustrations subject to change without notice and without incurring obligations.

Manufactured under license by Nortek Global HVAC, LLC, O'Fallon, MO. ®Registered Trademark/™ Trademark of Maytag Corporation or its related companies. © Nortek Global HVAC, LLC 2023. All rights reserved.

791F-0323 (Replaces 791F-0822)

Printed in U.S.A. (03/23)