

# SWITCH / DEVICE SELECTOR

## Mechanical

DEVICE	PATENT	APPLICATION								DMSS
		PRIMARY DRAIN LINES ONLY	PRIMARY DRAIN LINE OR PRIMARY DRAIN PAN (AUXILIARY OUTLET)	PRIMARY DRAIN PAN (AUXILIARY OUTLET) ONLY	PRIMARY DRAIN PAN (AUXILIARY OUTLET) & SECONDARY DRAIN PAN (2 PROBES)	PRIMARY DRAIN LINE (OR AUXILIARY OUTLET) & SECONDARY DRAIN PAN (2 PROBES)	SECONDARY DRAIN PAN ONLY	PRIMARY & SECONDARY DRAIN PANS (2 PROBES)	PRIMARY OR SECONDARY DRAIN PANS	
SS1 <sup>†</sup>	10,406,570	✓								
SS1P <sup>†*</sup>	10,406,570	✓								
SS2				✓						
SS2P <sup>†</sup>				✓						
SS3	6,698,215								✓	
SS3P <sup>†</sup>	6,698,215								✓	
EZT205 (contains trap)		✓								
EZT210 (contains trap)		✓								
EZT224				✓						
EZT225			✓							
EZT226				✓						
EZT230 (contains trap)		✓								
AG1100+ (metal only)	7,710,283						✓			
AG1200+	7,710,283						✓			
AG4200M <sup>†</sup> (drain outlet)	7,710,283 • 7,878,019 • 8,317,169						✓			

## Electronic

AG1250E	8,578,770						✓			
AG3150E <sup>†</sup>	8,151,580 • 8,561,417 • 8,578,770 • 7,774,395				✓					
AG3175E <sup>†*</sup>	8,151,580 • 8,561,417 • 8,578,770 • 7,774,395				✓					
AG3180E <sup>†*</sup>	8,578,770 • 7,744,395							✓		
AG4200E <sup>†</sup> (drain outlet)	8,578,770 • 8,317,169						✓			
SS610E	8,887,392									✓
SSW							✓			

## Cleanout

SCI	10,406,570	✓								
-----	------------	---	--	--	--	--	--	--	--	--

<sup>†</sup> Also a cleanout device  
<sup>°</sup> Plenum rated

<sup>^</sup> RectorSeal Goliath, Titan & Spartan drain pans only  
<sup>\*</sup> Able to handle 2 probes

# SWITCH / DEVICE FEATURES

## Mechanical

DEVICE	SENSOR TYPE	SWITCH TYPE		SENSING TECHNOLOGY		SUPPLY VOLTAGE	SWITCHING VOLTAGE	SWITCHING CURRENT			SWITCHING LOGIC		
	FLOAT	REED	MICROSWITCH	BUOYANCY / MAGNET	BUOYANCY	NOT NEEDED	0-24V	0 – 1.25 AMP (carry current, UL rating) 0 – 0.5 AMP (switching current)	0 – 4 AMP	0 – 5 AMP	NORMALLY CLOSED (NC)	NC ONLY w/NO Capability	NC / NO
SS1	✓	✓		✓		✓	✓	✓			✓		
SS1P	✓	✓		✓		✓	✓	✓			✓		
SS2	✓	✓		✓		✓	✓	✓			✓		
SS2P	✓	✓		✓		✓	✓	✓			✓		
SS3	✓	✓		✓		✓	✓	✓			✓		
SS3P	✓	✓		✓		✓	✓	✓			✓		
EZT205	✓		✓		✓	✓	✓		✓			✓	
EZT210	✓		✓		✓	✓	✓		✓			✓	
EZT224	✓		✓		✓	✓	✓		✓			✓	
EZT225	✓		✓		✓	✓	✓		✓			✓	
EZT226	✓		✓		✓	✓	✓		✓			✓	
EZT230	✓		✓		✓	✓	✓		✓			✓	
AG1100	✓		✓	✓		✓	✓			✓			✓
AG1200	✓		✓	✓		✓	✓			✓			✓
AG4200M	✓		✓	✓		✓	✓			✓			✓

## Electronic

DEVICE	SENSOR TYPE	SWITCH TYPE	SENSING TECHNOLOGY	SUPPLY VOLTAGE		SWITCHING VOLTAGE		SWITCHING CURRENT	SWITCHING LOGIC
	METAL PINS/PROBE	RELAY	WATER RESISTANCE	24VAC	110 – 230VAC	0 – 24V	0 – 250V	0 – 5 AMP	NC / NO
AG1250E	✓	✓	✓	✓		✓		✓	✓
AG3150E	✓	✓	✓	✓		✓		✓	✓
AG3175E	✓	✓	✓	✓		✓		✓	✓
AG3180E	✓	✓	✓	✓		✓		✓	✓
AG4200E	✓	✓	✓	✓		✓		✓	✓
SS610E	✓	✓	✓		✓		✓	✓	✓
SSW	✓	✓	✓	✓		✓		✓	✓