



### Suction Accumulators

- Specifically designed for heat pumps
- Solid copper connections
- "U" tube design for maximum flow of refrigerant and minimum oil entrapment
- Powder paint exterior coating surpasses 500 hour ASTM salt spray tests
- Integral 430°F fusible plugs
- Capacity rating listed below is holding capacity, in ounces, of R22 at 40°F; divide by 0.7 to obtain recommended maximum system charge on fixed orifice systems

Order #	Mfg. #	R22 Capacity	Diam.	Height	Conn. Size	Wt. Lbs.	Each
B82-098	VA314S	35	3"	10-3/8"	1/2" ODF	3.0	229.00
B82-099	VA315S	35	3"	10-3/8"	5/8" ODF	3.0	255.00
B82-100	VA355S	55	3"	15"	5/8" ODF	4.0	265.00
B82-101	VA356S	55	3"	15"	3/4" ODF	3.5	259.00
B81-391	PA-4065-9-5C	60	4"	9-5/8"	5/8" ODF	4.0	295.00
B13-668	PA4065-9-6C	58	4"	9-5/8"	3/4" ODF	3.5	275.00
B81-392	VPA589-6SRD	89	5"	9-5/8"	3/4" ODF	5.0	295.00
B13-671	VPA589-7SRD	86	5"	9-5/8"	7/8" ODF	5.0	299.00
B13-669	VPA5811-6SRD	111	5"	11-3/8"	3/4" ODF	5.5	315.00
B13-670	VPA5811-7SRD	108	5"	11-3/8"	7/8" ODF	5.0	325.00
B81-393	VPA5812-7SRD	125	5"	12-7/8"	7/8" ODF	7.0	329.00
B82-102	VPA5815-7SRD	156	5"	15-3/8"	7/8" ODF	6.5	335.00
B82-103	VPA5817-7SRD	179	5"	17-1/4"	7/8" ODF	5.0	379.00
B82-104	VA610-9SRD	211	6"	15"	1-1/8" ODF	18.0	609.00
B82-105	VA611-11SRD	214	6"	15-1/4"	1-3/8" ODF	20.0	655.00
B82-106	VA611-9SRD	264	6"	18"	1-1/8" ODF	21.0	645.00
B82-107	VA615-11SRD	302	6"	20-1/4"	1-3/8" ODF	24.0	689.00



### Suction Accumulators Vertical Mount

- Acts as temporary holding vessel between evaporator outlet and compressor inlet
- Traps liquid charge and allows it to be evaporated and fed to compressor at a controlled rate
- Internal U-tube includes an orifice which ensures proper metering of oil back to compressor
- Welded and brazed design for higher strength
- Nickel plated connections
- Screened orifice for proper oil return
- Powder paint finish
- UL fusible plug rated to 430°F

Order #	Mfg. #	R134a Capacity	R22 Capacity	R404A/R507 Capacity	Diam.	Height	Conn. Size	Wt. Lbs.	Each
B81-388	A5-07B	6	6	5	5"	13"	7/8" ODF	11	535.00
B81-389	A6-11W	12	12	10	6"	15"	1-1/8" ODF	13	515.00
B81-390	A6-13Z	18	17.5	15	6"	20-1/4"	1-3/8" ODF	18	539.00
B81-686	A6-15	15	14.5	12.5	6"	24-3/4"	1-5/8" ODF	23	655.00
B81-687	A8-21	29.5	29	25	8-5/8"	20-1/8"	2-1/8" ODF	41	1445.00



### Receivers Vertical Mount

- Holds excess refrigerant between condenser and expansion device
- Designed with liquid capacities in accordance with ASHRAE standards
- Maximum working pressure of 450 PSI
- Powder paint finish
- Includes rotolock valve

Order #	Mfg. #	R134a Capacity	R22 Capacity	R404A/R507 Capacity	Diam.	Height	Conn. Size	Wt. Lbs.	Each
B81-385	R35-01S	2.5	2.5	2	3-1/2"	7-1/2"	1/4" SAE x 1/4" SAE	3	335.00
B81-386	R5-01	6.5	6.5	5.5	5"	10"	3/8" SAE x 3/8" SAE	8	385.00
B81-387	R6-01	12	11.5	10	6"	12"	3/8" SAE x 3/8" SAE	11	399.00
B81-688	R6-02	17.5	17.25	15	6"	18"	1/2" SAE x 1/2" SAE	17	475.00