

Coleman® COMMERCIAL PRODUCTS

Packaged and Split DX Systems



Coleman® heating and air conditioning products have been trusted in the world's most prestigious buildings – and that same commitment to strength, durability and innovation can be found in every commercial unit we build. Coleman® commercial ducted systems deliver performance, efficiency and reliability you can trust. And with a complete family of products to choose from, there's a system perfectly suited to provide optimal comfort, exceptional energy savings and lasting performance.



**HEATING AND
AIR CONDITIONING**



Coleman® Commercial Rooftop Units

| Series Name (Nominal Tonnage) | Nomenclature | Standard Efficiency* | High Efficiency* | Ultra-high Efficiency* | Warranties | Smart Equipment | Highlights |
|--|--|---|---|---|---|-----------------|--|
| Apex™ (3-6 tons) | A/C (cooling, gas, electric) ZE (3-6 tons) HP XN (3-5 tons) | (ZE) 3-6T: Up to 12.0 EER/ 14.0 SEER/15.0 IEER (XN) 3-5T: Up to 12.0 EER/ 14.0 SEER, 3.35 COP | — | — | | | Commercial-grade packaged units in rugged, compact design |
| Coleman® Point™ Core (3-12.5 tons) | A/C (cooling, gas, electric) ZQ: Std. Eff. (3-5 tons) ZX: Std. Eff. (6 tons) ZY: High Eff. (3-10 tons) ZL: 3 Stage High Eff. (3-5, 7.5-12.5 tons) HP XQ: Std. Eff. (3-5 tons) XX: Std. Eff. (6-10 tons) XY: High Eff. (3-8.5 tons) | (ZQ) 3-5T: Up to 12.2 EER/ 14.1 SEER (ZX) 6T: Up to 11.2 EER/ 14.8 IEER (XQ) 3-5T: Up to 12.25 EER/ 14.5 SEER, 8.3 HSPF (XX) 6-10T: Up to 11.8 EER/ 15.1 IEER, 3.5 COP | (ZY) 3-5T: Up to 12.0 EER/ 15.4 SEER 6-10T: Up to 12.2 EER/ 16.0 IEER (ZL) 3-5T: Up to 13.2 EER/ 17.2 SEER 7.5-12.5T: Up to 12.2 EER/ 16.3 IEER (XY) 3-5T: Up to 12.5 EER/ 15.0 SEER, 8.2 HSPF 6-8.5T: Up to 12.1 EER/ 16.5 IEER, 3.5 COP | — | 15-year stainless steel heat exchanger limited 10-year aluminized heat exchanger limited | | The go-to unit for 3-12.5T jobs Sits directly on many competitive curbs without bulky adaptors Perfect for new construction and replacement applications |
| Coleman® Point™ Pro (3-12.5 tons) | A/C (cooling, gas, electric) ZJ: High Eff. (3-12.5 tons) ZB: 3 Stage High Eff. (6.5-12.5 tons) ZT: Ultra-high Eff. (3-12.5 tons) HP XP: Std. Eff. (6.5-12.5 tons) | (XP) 6.5-12.5T: Up to 12.0 EER/15.2 IEER, Up to 3.5 COP | (ZJ) 3-5T: Up to 12.2 EER/ 15.0 SEER 6.5-12.5T: Up to 12.2 EER/ 15.2 IEER (ZB) 6.5-12.5T: Up to 12.2 EER/ 16.0 IEER | (ZT) 3-5T: Up to 14.0 EER/ 17.5 SEER 6.5-12.5T: Up to 13.1 EER/ 21.2 IEER | 5-year electric heat exchanger limited 5-year compressor limited 1-year parts limited | Yes | Highest efficiency, dual-circuit unit options Designed with servicer in mind Premium standard features, like slide-out blowers and hinged, toolless access panels |
| Coleman® Point™ Choice (12.5-27.5 tons) | A/C (cooling, gas, electric) CD: High Eff. Vertical (15-27.5 tons) A/C (cooling, gas, electric) CS/CK: High Eff. Horiz (15-25 tons) HP PD: High Eff. Vertical (12.5-25 tons) A/C (cooling, gas, electric) CE: Ultra-high Eff. Vertical (12.5-23 tons) | — | (CD) 15-20T: Up to 11.1 EER/ 14.8 IEER 25-27.5T: Up to 10.4 EER/ 14.4 IEER (CS/CK) 15-20T: Up to 11.1 EER/ 14.8 IEER 25T: Up to 10.2 EER/ 14.4 IEER (PD) 12.5-25T: Up to 10.9 EER/ 14.0 IEER, Up to 3.3 COP | (CE) 12.5-20T: Up to 12.7 EER/ 20.3 IEER 23T: Up to 11.3 EER/ 18.8 IEER | | | HE models exceed DOE 2023 part-load standards by almost 10% UHE models exceed DOE 2023 part-load standards by 45% IntelliSpeed™, single-zone VAV and VAV airflow options Direct replacement of most competing units without a transition curb Up to 33% lighter than existing Coleman® models, and up to 22% lighter than competing products |

*Maximum values of efficiency may vary depending on tonnage and options.



Coleman® Split System Air Conditioners, Heat Pumps and Air Handlers

| | Coleman® Air Conditioners | Coleman® Heat Pumps | Coleman® Air Handlers | |
|------------------------|---|--|--|----------------------------|
| Tonnage Range | 7.5-25 tons Up to 11.4 EER/16.0 IEER | 7.5-20 tons Up to 11.0 EER/16.0 IEER | 7.5-25 tons Designed to match up with split system AC/heat pumps 2,250-12,500 CFM | |
| | YK-2 pipe (7.5 tons) YH-2 pipe (10-25 tons) | PK-2 pipe (7.5 tons) PH-2 pipe (10-15 tons) | NH-2 pipe (25 tons only) | NS-2 pipe (7.5-20 tons) |
| | YJ-4 pipe (10-20 tons) | PJ-4 pipe (15-20 tons) | — | NW-4 pipe (7.5-20 tons) |
| Smart Equipment | Yes | | | |
| Warranties | 5-year Compressor Limited Warranty 1-year Parts Limited Warranty | | 1-year Parts Limited Warranty | |



Coleman® Energy Recovery Ventilators (ERVs)

| | Energy Recovery Ventilators |
|----------------------|---|
| Tonnage Range | 2-50 tons |
| Warranties | 1-year Parts Limited Warranty |
| Efficiency | 300-13,000 CFM 63%-73% effectiveness |



Verasys Smart Controls

Verasys configurable controls create an easy-to-use, easy-to-install solution to help maximize HVAC investments for your customers. Convenient centralized building control, coupled with remote access and monitoring, enables the building to operate more efficiently and is delivered in a scalable, cost-effective way.





Coleman® Residential Package Equipment - Light Commercial Application

| | Air Conditioners | | Heat Pumps | |
|------------------------------|---|-----------------------------------|---|---|
| | Energy Star Certified 15.2 SEER2 | Standard Efficiency 13.4 SEER2 | Energy Star Certified 15.2 SEER2 | Standard Efficiency 13.4 SEER2 |
| Models | PCE6, PCG6 | PCE4, PCG4 | PHE6, PHG6 | PHE4, PHG4 |
| Tonnage Range | 2-5 Tons | | 2-5 Tons | |
| Efficiency | 15.2 SEER2/ 81% AFUE (PCG6)  | 13.4 SEER2/ 81% AFUE (PCG4) | 15.2 SEER2/7.2 HSPF2 81% AFUE (PHG6)  | 13.4 SEER2/6.7 HSPF2 81% AFUE (PHG4) |
| Heating/Cooling Stage | Two-Stage | Single-Stage | Two-Stage | Single-Stage |
| Phase | Single- and Three-Phase | | Single- and Three-Phase* | |
| Warranties | 10-year Heat Exchanger Limited Warranty (PCG6/PCG4) 5-year Compressor Limited Warranty 1-year Parts Limited Warranty 30-day Labor Limited Warranty | | 10-year Heat Exchanger Limited Warranty (PHG6/PHG4) 5-year Compressor Limited Warranty 1-year Parts Limited Warranty 30-day Labor Limited Warranty | |

*PHG6/PHG4 are single-phase only



Certain **light commercial rooftop models** meet ENERGY STAR® requirements for energy efficiency. For a complete list, visit energystar.gov.