

Inverter Driven Heat Pump

18,000 BTU Multi Zone System

Job Name \_\_\_\_\_  
 Location \_\_\_\_\_  
 Engineer \_\_\_\_\_  
 Submitted To \_\_\_\_\_  
 Submitted By \_\_\_\_\_  
 Reference \_\_\_\_\_

Date \_\_\_\_\_  
 Approval \_\_\_\_\_  
 Construction \_\_\_\_\_  
 Unit No \_\_\_\_\_  
 Drawing No \_\_\_\_\_

**PRODUCT FEATURES**

Operate as few as one indoor unit or all indoor units  
 Mix & match from 4 indoor unit styles  
 Blue-fin condenser coil coating



MODEL NUMBERS			
Outdoor Unit	AOU18RLXFZ		
System	18RLXFZ		
EFFICIENCIES			
Indoor Unit Type	Non - Ducted	Ducted	Mix
SEER	18	16	17
SEER2	18	16.3	17.15
EER	12.5	12.1	12.3
EER2	12.5	12.1	12.3
HSPF	9.3	9.0	9.2
HSPF 2 (IV) / HSPF 2 (V)	8.7/6.8	8.7/6.9	8.7/6.8
COP	3.44	3.52	3.48
COP	Btu/hW	11.7	12.0
COP2	3.44	3.52	3.48
COP2	Btu/hW	11.7	12.0
OUTDOOR TEMPERATURE OPERATION RANGE			
Cooling	*F(*C)	14 to 115 (-10 to 46)	
Heating		5 to 75 (-15 to 24)	
CAPACITIES			
Total Capacity Range			14,000 - 21,000
Cooling	Rated	Btu/h	18,000
	Min.-Max.		6,100 - 21,000
Heating	Rated		22,000
	Min.-Max.		6,800 - 24,000
LINESET REQUIREMENTS			
Connection Method	Flare		
Liquid	in (mm)	Ø1¼ (Ø6.35) × 2	
Gas		Ø3/8 (Ø9.52) × 2	
Pre-charge length (Total)		ft (m)	98 (30)
Max. length (Total)			164 (50)
Max. length (Each)			82 (25)
Min. length (Total)			49 (15)
Min. length (Each)			16 (5)
Max. height difference			49 (15)
Max. height difference between indoor units		33 (10)	
OUTDOOR DIMENSIONS & WEIGHT			
Net (H x W x D)	in (mm)	27-9/16 × 35-7/16 × 13 (700 × 900 × 330)	
Gross (H x W x D)		34-1/16 × 41-5/16 × 17-1/2 (865 × 1,050 × 445)	
Net Weight	lb (kg)	119 (54)	
Gross Weight		137 (62)	

**Warranty Information**



7 Year Compressor, 5 Year Parts out-of-the-box Warranty

10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence

12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence, and installed by a Fujitsu Elite contractor

**SOUND PRESSURE**

Outdoor Unit	Cooling	Heating	dB (A)
			49
			49

**FAN DATA**

Outdoor Unit	Cooling	Heating	CFM (m3/h)
Airflow rate			1,795 (3,050)
			1,795 (3,050)

**ELECTRICAL SPECIFICATIONS**

Indoor Unit Type	Non - Ducted	Ducted	Mix
Voltage/Frequency/Phase	1Ø 208/230 V 60 Hz		
Available Voltage Range	187-264V		
Current	Cooling	6.3	6.6
	Heating	8.2	8
Maximum Operating Current	10		
Starting current	8.2		
MCA	A		
Maximum Circuit Breaker	15		
Rated Input Power	Cooling	1.44	1.49
	Heating	1.87	1.83
Max. Input Power	Cooling	2.06	2.14
	Heating	2.1	2.08


Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation <https://connect.fujitsugeneral.com>

Effective Date: 1/10/2023

CONNECTABLE INDOOR UNITS	
TYPE	Slim Duct (ADUH)
	Wall Mount (ASU/ASUH)
	Compact Cassette (ACUH)
	Floor Mount (AGU)
NUMBER	2
DIMENSIONS:	

REFRIGERANT		
Type	R410A	
Charge	lb oz	4 lb 14 oz
	g	2,200
Oil Type	POE	

Units: In. (mm)



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Airstage logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2022 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:  
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit).