

Inverter Driven Heat Pump

12,000 BTU Single Zone Wall Mounted System

Job Name _____
 Location _____
 Engineer _____
 Submitted To _____
 Submitted By _____
 Reference _____

Date _____
 Approval _____
 Construction _____
 Unit No _____
 Drawing No _____

PRODUCT FEATURES

- Auto Changeover
- 24 hr. Timer
- Auto Louver: Up/Down
- Minimum Heat Mode
- Wireless Remote Control Included
- 2-Wire control Compatible
- 2 Communication (UART) Ports
- BACnet Compatible
- Modbus Compatible



MODEL NUMBERS		
Indoor Unit	ASUH12LMAS	
Outdoor Unit	AOUH12LMAS1	
System	12LMAS1	
EFFICIENCIES		
SEER	23	
SEER 2	23	
EER	12.5	
EER 2	12.5	
HSPF	12.1	
HSPF 2	11.1	
COP	kW/kW 4.12	
COP	Btu/hW 14.1	
COP2	kW/kW 4.12	
COP2	Btu/hW 14.1	
OUTDOOR TEMPERATURE OPERATION RANGE		
Cooling	*F(°C) 14 to 115 (-10 to 46)	
Heating	5 to 75 (-15 to 24)	
CAPACITIES		
Cooling	Rated	12000
	Min.-Max.	3,400-13,300
Heating	Rated	14500
	Min.-Max.	2,800-19,100
LINESET REQUIREMENTS		
Connection Method		Flare
Liquid	in (mm)	Ø1/4 (Ø6.35)
Gas	in (mm)	Ø3/8 (Ø9.52)
Pre-charge length	ft (m)	49 (15)
Minimum Length	ft (m)	10 (3)
Max. length	ft (m)	66 (20)
Max. height difference	ft (m)	49 (15)
INDOOR DIMENSIONS & WEIGHT		
Net (H x W x D)	in (mm)	10-5/8 x 32-13/16 x 8-3/4 (270 x 834 x 222)
Gross (H x W x D)	in (mm)	10-7/8 x 36 x 13-1/16 (277 x 914 x 332)
Net Weight	lb (kg)	22 (10)
Gross Weight	lb (kg)	29 (13)
OUTDOOR DIMENSIONS & WEIGHT		
Net (H x W x D)	in (mm)	21-5/16 x 31-7/16 x 11-7/16 (542 x 799 x 290)
Gross (H x W x D)	in (mm)	23-11/16 x 37 x 14-3/4 (602 x 940 x 375)
Net Weight	lb (kg)	71 (32)
Gross Weight	lb (kg)	77(35)

Warranty Information



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence, and installed by a Fujitsu Elite contractor

ACCESSORIES

UTY-RNRUZ*	Wired remote controller
UTY-RSRY	Simple remote controller
UTY-RHRY	Simple remote controller
UTY-XWZX	External Connect Kit
UTY-XWZXZ5	External Connect Kit
UTY-XCSXZ2	External Input and Output PCB
UTY-TWRXZ2	Communication Kit
UTY-TFSXF1	Wireless LAN adapter
UTY-VMSX	Modbus Converter
UTY-TTRXZ1	24V Thermostat Converter
UTY-VTGX	Network Converter



This system combination is Energy Star qualified



+App available in Apple® App Store and Google® Play Store.

Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation <https://connect.fujitsugeneral.com>

Effective Date: 10/31/2022

Inverter Driven Heat Pump

12,000 BTU Single Zone Wall Mounted System


FAN DATA			
Indoor Unit Airflow rate	Cooling	HIGH	453 (770)
		MED	353 (600)
		LOW	265 (450)
		QUIET	147 (250)
	Heating	HIGH	453 (770)
		MED	377 (640)
		LOW	306 (520)
		QUIET	182 (310)
Outdoor Unit Airflow rate	Cooling	1,065 (1,810)	
	Heating	1,065 (1,810)	
SOUND PRESSURE			
Indoor Unit	Cooling	HIGH	43
		MED	36
		LOW	30
		QUIET	19
	Heating	HIGH	43
		MED	38
		LOW	33
		QUIET	21
Outdoor Unit	Cooling	49	
	Heating	51	
REFRIGERANT			
Type			R410A
Charge	lb oz	2 lb 3 oz	
	g	1000	
Oil Type			RB68A

ELECTRICAL SPECIFICATIONS			
Voltage/Frequency/Phase		208/230 V- 60 Hz	
Available Voltage Range		187-253 V	
Current	Cooling	Rated	4.7
	Heating	Rated	4.9
Maximum Operating Current	Cooling	A	6.9
	Heating		9.4
Starting Current		6	
MCA		11.5	
Maximum Circuit Breaker		15	
Input Power	Cooling	Rated	kW
		Min.-Max.	
	Heating	Rated	
Power Factor	Cooling	%	88.8
	Heating		91.4
OTHER			
Moisture Removal		pints/h (L/h)	3.8 (1.8)
Energy Star		Yes	
Drain hose	Material	PP+HDPE	
	Tip diameter	in (mm)	Ø17/32 (Ø13.8) (I.D.), Ø19/32 to 21/32 (Ø15.0 to 16.8) (O.D.)
Operation Range	Cooling	°F (°C)	64 to 90 (18 to 32)
	Heating	%RH	80 or less
		°F (°C)	60 to 86 (16 to 30)

DIMENSIONS:

Units: In. (mm)


Wall Bracket Data:




DIMENSIONS

Units: In. (mm)

Indoor Unit



Outdoor Unit



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Airstage logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2022 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit).