

Climate 5000 Series
36K BTU Multi Zone Max Performance
Outdoor Unit

Engineering
Submittal
Sheet



BOSCH

Overview and Project Information



AHRI CERTIFIED
AIRCRAFT AIR CONDITIONING & REFRIGERATION INSTITUTE

UL
LISTED

Project Name	
Location	
Architect	
Engineer	
General Contractor	
Reference #	
Date	

36K Btu Multi Zone Max Performance Outdoor Unit

Outdoor part number	8733956227		
Outdoor model number	BMS500-AAM036-1CSXHC		
Efficiency Data	Ducted	Non-Ducted	Mixed Ducted & Non-Ducted
SEER2	19.0	22.2	20.6
EER2	11.7	13.6	12.7
HSPF2 (Region IV)	10	10.3	10.2
HSPF2 (Region V)	8.1	8.3	8.2
COP(47°F)	3.9	3.9	3.9
COP(5°F)	1.7	1.9	1.8
Performance Data	Ducted	Non-Ducted	Mixed Ducted & Non-Ducted
Cooling	Capacity Range (Btu/h)	17400-44000	17900-42000
	Rated Capacity (Btu/h)	36000	36000
	Current (A)	14.20	11.80
	Input Power (W)	3180	2650
Heating	Capacity Range (Btu/h)	13300-52000	12500-51300
	Rated Capacity (47°F)	37000	37000
	Capacity (5°F)	33000	36000
	Current (A)	12.20	12.00
	Input Power (W)	2795	2780

Operation Range		
ODU	Cooling (°F / °C)	-22~122 / -30~50
	Heating (°F / °C)	-22~86 / -30~30
Electrical Data		
	Power supply (V / Ø / Hz)	208-230 / 1 / 60
	Min. circuit ampacity (A)	40.0
	Max. fuse (A)	60.0

Compressor Data	
Type:	Rotary
Refrigerant oil /oil charge (ml)	VG74/1400
Input (W)	3040
Rated current (A)	26

Climate 5000 Series
36K Btu Multi Zone Max Performance Outdoor Unit



BOSCH

Piping	
Refrigerant precharge (ft / m)	98 / 30
Refrigerant charge (oz / g)	162/4600
Liquid side (in / mm)	1/4" / Ø6.35 (Qty. 4)
Gas side (in / mm)	3/8" / Ø9.52 (Qty. 3) 1/2" / Ø12.7 (Qty. 1)
Additional charge per ft - liquid side (oz / g)	0.161 / 15
Additional charge per ft - gas side (oz / g)	0.322 / 30
Max. refrigerant pipe length (ft / m)	262 / 80
Max. length to one IDU (ft / m)	115 / 35
Max. height difference between IDU and ODU (ft / m)	49 / 15
Max. height difference between IDU's (ft / m)	33 / 10

System Data	
Refrigerant type	R410A
Design pressure (PSIG)	550/340
Dehumidification (pts/hr)	8.45
ODU	Fan motor model #
	ZKFN-85-8-22-5
	Fan motor qty (ea)
	2
	Fan motor input (W)
	126.0
	Fan motor speed, H / M / L (RPM)
	800 / 700 / 600
IDU	Air flow, max (CFM)
	4500
	Noise level, max (dB(A))
	63.0
	Net weight (lbs / kg)
	223.77 / 101.5
	Gross weight (lbs / kg)
	255.07 / 115.7
IDU	Minimum # of indoors
	2
IDU	Maximum # of indoors
	4

Multi Zone Pairing Information	2 ZONE	3 ZONE	4 ZONE	5 ZONE
BMS500-AAM036-1CSXHC	6k + 18k	6k + 6k + 12k	6k + 6k + 6k + 6k	
	6k + 24k	6k + 6k + 18k	6k + 6k + 6k + 9k	
	9k + 18k	6k + 6k + 24k	6k + 6k + 6k + 12k	
	9k + 24k	6k + 9k + 12k	6k + 6k + 6k + 18k	
	12k + 12k	6k + 9k + 18k	6k + 6k + 6k + 24k	
	12k + 18k	6k + 9k + 24k	6k + 6k + 9k + 9k	
	12k + 24k	6k + 12k + 12k	6k + 6k + 9k + 12k	
	18k + 18k	6k + 12k + 18k	6k + 6k + 9k + 18k	
	18k + 24k	6k + 12k + 24k	6k + 6k + 9k + 24k	
	24k + 24k	6k + 18k + 18k	6k + 6k + 12k + 12k	
		6k + 18k + 24k	6k + 6k + 12k + 18k	
		9k + 9k + 9k	6k + 6k + 12k + 24k	
		9k + 9k + 12k	6k + 9k + 9k + 9k	
		9k + 9k + 18k	6k + 9k + 9k + 12k	
		9k + 9k + 24k	6k + 9k + 9k + 18k	
		9k + 12k + 12k	6k + 9k + 9k + 24k	
		9k + 12k + 18k	6k + 9k + 12k + 12k	
		9k + 12k + 24k	6k + 9k + 12k + 18k	
		9k + 18k + 18k	6k + 12k + 12k + 12k	
		12k + 12k + 12k	6k + 12k + 12k + 18k	
		12k + 12k + 18k	9k + 9k + 9k + 9k	
		12k + 12k + 24k	9k + 9k + 9k + 12k	
		12k + 18k + 18k	9k + 9k + 9k + 18k	
			9k + 9k + 12k + 12k	
			9k + 9k + 12k + 18k	
			9k + 12k + 12k + 12k	
			12k + 12k + 12k + 12k	




Bosch Thermotechnology Corp.
Londonderry, NH • Watertown, MA • Ft. Lauderdale, FL

Climate 5000 Series
36K Btu Multi Zone Max Performance Outdoor Unit



BOSCH

Outdoor Unit Dimensions and Connections



Model	W (in)	D (in)	H (in)	W1 (in)	H1 (in)	H2 (in)	H3 (in)	A (in)	B (in)	C (in)
BMS500-AAM036-1CSXHC	37.5	16.3	52.5	41.7	13.4	3.3	5.2	25	15.9	17.6