



### Cabinet & Duct Dimensions

Model	Nominal CFM (m <sup>3</sup> /min)	Cabinet Size	Cabinet Dimensions (Inches)			Approximate Operating Weights
			A	B	C	Lbs
TM9Y040A10MP11	1000	A	14-1/2	13-3/8	11-3/4	113
TM9Y060B12MP11	1200	B	17-1/2	16-3/8	13-1/4	119
TM9Y080B12MP11	1200	B	17-1/2	16-3/8	14-3/4	123
TM9Y080C16MP11	1600	C	21	19-7/8	16-1/2	130
TM9Y100C16MP11	1600	C	21	19-7/8	18-1/4	136
TM9Y100C20MP11	2000	C	21	19-7/8	18-1/4	143
TM9Y120D20MP11	2000	D	24-1/2	23-3/8	21-3/4	154

### Ratings & Physical / Electrical Data

Model	Input High/Low	Output High/Low	Total Unit	AFUE	High Fire Air Temp. Rise	Low Fire Air Temp. Rise
	MBH	MBH	Amps	%	°F	°F
TM9Y040A10MP11	40/26	38/25	9.5	96	25-55	25-55
TM9Y060B12MP11	60/39	58/37	9.5	96	35-65	35-65
TM9Y080B12MP11	80/52	77/50	9.5	96	45-75	35-65
TM9Y080C16MP11	80/52	77/50	9.5	96	40-70	25-55
TM9Y100C16MP11	100/65	96/62	9.5	96	50-80	30-60
TM9Y100C20MP11	100/65	96/62	10.9	96	45-75	30-60
TM9Y120D20MP11	120/78	115/75	10.9	96	50-80	45-75
Model	Max. Outlet Air Temp.	Blower	Blower Size		Max. Over-current Protect	Min. Wire Size (awg) @ 75 ft. One Way
	°F	HP	Amps	In.		
TM9Y040A10MP11	190	1/2	6.8	11 X 8	15	14
TM9Y060B12MP11	190	1/2	6.8	11 x 8	15	14
TM9Y080B12MP11	190	1/2	6.8	11 x 8	15	14
TM9Y080C16MP11	190	1/2	6.8	11 x 10	15	14
TM9Y100C16MP11	190	1/2	6.8	11 x 10	15	14
TM9Y100C20MP11	190	3/4	8.4	11 x 11	15	14
TM9Y120D20MP11	190	3/4	8.4	11 x 11	15	14

Annual Fuel Utilization Efficiency (AFUE) numbers are determined in accordance with DOE Test procedures.

Wire size and over current protection must comply with the National Electrical Code (NFPA-70-latest edition) and all local codes.

The furnace shall be installed so that the electrical components are protected from water.