



The AM-1 Series Thermostatic Mixing Valve with Temperature Gauge

FASTER SETUP AND CHECKOUT



AM-1 Series Thermostatic Mixing Valve with Temperature Gauge

Offer your customers a solution to scalding water and bacteria growth.

The AM-1 Series Mixing Valve with Temperature Gauge is a solution for both residential and commercial water heater systems. It makes installation checkout and troubleshooting faster than ever thanks to the integrated temperature dial readout. It lets homeowners store water at 140° F and higher to help prevent bacteria growth, but delivers comfortable water temperatures at around 120° F when they turn on sinks, showers, and tubs.

Integrated Temperature Gauge

Its special temperature dial readout speeds up checkout and troubleshooting.

Accurate Temperature

Lockable hand wheel for precise temperature control.

Easy Installation

Multiple connection options including a Union Sweat adapter for easy attachment and Push Connect support.

Protection

Designed to prevent scalding water and legionella bacteria growth by storing water at 140° F and higher, but delivering comfortable water temperatures out of the faucet at about 120° F.

Meets Safety Certifications

Complies with all necessary industry certifications including ASSE 1070, ASSE 1017, CSA, and IAPMO.

Fewer Callbacks

Teflon® coating helps the valve last longer and reduce callbacks.



For more information

resideo.com



Resideo Technologies, Inc.

1985 Douglas Drive North
Golden Valley, MN 55422
1-800-468-1502
resideo.com

MODEL #	PRODUCT DESCRIPTION
AM1-TG100-US-LF/U	1/2" Sweat Tail PC with Temperature Gauge
AM1-TG101-US-LF/U	3/4" Sweat Tail PC with Temperature Gauge
AM1-TG102-US-LF/U	1" Sweat Tail PC with Temperature Gauge
AM100-SB-1LF/U	1/2" Lead Free Mixing Valve with Push Connect
AM100-SB/U	1/2" Push Connect NPT Fittings 3X
AM100-USTG-1LF/U	1/2" Low Lead TMV 100-145F, Union with Temperature Gauge
AM100C-USTG-1LF/U	1/2" Low Lead TMV 80-120F, Union with Temperature Gauge
AM100C1070-SB-1LF	1/2" Lead Free 1070 Mixing Valve with Push Connect
AM100C1070-USTG1LF	1/2" Low Lead TMV 70-120F, Union with Temperature Gauge
AM100R-USTG-1/U	1/2" TMV 70-180F, Union with Temperature Gauge
AM101-SB-1LF/U	3/4" Lead Free Mixing Valve with Push Connect
AM101-SB/U	3/4" Push Connect NPT Fittings 3X
AM101-USTG-1LF/U	3/4" Low Lead TMV 100-145F, Union with Temperature Gauge
AM101C-USTG-1LF/U	3/4" Low Lead TMV 80-120F, Union with Temperature Gauge
AM101C1070-SB-1LF	3/4" Lead Free 1070 Mixing Valve with Push Connect
AM101C1070-USTG-LF	3/4" Low Lead TMV 70-120F, Union with Temperature Gauge
AM101R-USTG-1/U	3/4" TMV 70-180F, Union with Temperature Gauge
AM102-SB-1LF/U	1" Lead Free Mixing Valve with Push Connect
AM102-SB/U	1" Push Connect NPT Fittings 3X
AM102-USTG-1LF/U	1" Low Lead TMV 100-145F, Union with Temperature Gauge
AM102C-USTG-1LF/U	1" Low Lead TMV 80-120F, Union with Temperature Gauge
AM102C1070-SB-1LF	1" Lead Free 1070 Mixing Valve with Push Connect
AM102C1070-USTG-LF	1" Low Lead TMV 70-120F, Union with Temperature Gauge
AM102R-USTG-1/U	1" TMV 70-180F, Union with Temperature Gauge
TG200-UT/U	Thermometer, 2" dial, 1/2" threaded well
TG250-UT/U	Thermometer, 2.5" dial, 1/2" threaded well

03-00367 | SC | 02/20

© 2020 Resideo Technologies, Inc. All rights reserved.

The Honeywell Home trademark is used under license from Honeywell International, Inc.

This product is manufactured by Resideo Technologies, Inc., and its affiliates. Golden Valley, MN 55422

Honeywell Home