

# Solid Surface Shower Bases

## SMFSL Low Profile End & Center Drains

### FEATURES

- Solid material all the way through which is cast as a single piece.
- Aluminum Hydroxide (Bauxite) combined with pure acrylic polyester resin creates a homogenous material that is super dense and consistent throughout the base. This results in a product that is easy to repair, soft to the touch, and features gentle matte surfaces that will not support bacteria growth.
- Extremely low 2" curb height for a sleek, modern look. Once the underlayment and tile are installed, there is about a 1" effective curb height for easy entry and exits.
- A wide 3-1/2" threshold depth to hold the modern barn door style shower doors. Also includes an integral 1" high tiling flange for a waterproof installation.
- Unique curving drain cover on end drain models and a round drain cover on the center drain model, in same color as base, conceal a shower drain. They also eliminate the need for decorative drain covers to match faucetry. Drain not included.
- 10 Year Limited Residential Warranty / 3 Year Commercial Warranty



### Specify Model

		Drain Location			Lgth	Width	HT.	A	B
SIZE		Left	Right	Center					
<input type="checkbox"/> 36" x 36" x 2"				SMFSL3636C	36"	36"	2"	19"	17"
<input type="checkbox"/> 48" x 34" x 2"	SMFSL4834L	SMFSL4834R			48"	34"	2"	18"	16"
<input type="checkbox"/> 60" x 32" x 2"	SMFSL6032L	SMFSL6032R			60"	32"	2"	17"	15"
<input type="checkbox"/> 60" x 36" x 2"	SMFSL6036L	SMFSL6036R			60"	36"	2"	19"	17"

### To Be Specified: Color

<input type="checkbox"/> 01 White			
<input type="checkbox"/> 87 Concrete			
<input type="checkbox"/> 02 Cameo	White 01	Concrete 87	Cameo 02

### Compliance Certifications - Meets or Exceeds the Following Specifications

- IGC 154-2012
- ASME A112.18.1 / CSA B125.125.1-11
- ASTM 1028-96 coefficient of friction test (minimum rating of 0.67)
- IAPMO
- cUPC®

