



## Wellworth® Classic

Two-piece elongated toilet, 1.6 gpf  
**K-3505**

### Features

- Elongated bowl offers added room and comfort
- Equipped with Sloan FLUSHMATE® – Sloan® Valve Company
- 1.6 gpf (6.0 lpf)
- 12" x 10" (305 mm x 254 mm) water surface
- Left-hand Polished Chrome trip lever

### Installation

- Seat and supply line sold separately
- Standard 12" (305 mm) rough-in

### Recommended Products/Accessories

K-5588 Purefresh® Deodorizing elongated toilet seat  
K-4108 PureWash® E750 Elongated bidet toilet seat with remote control  
K-5420 Low-Profile Bolt Caps

### Included Components

K-4645 Toilet tank, 1.6 gpf  
K-4303 Elongated toilet bowl  
K-9481-L Left-hand trip lever for KOHLER® toilets



### Codes/Standards




ASME A112.19.2/CSA B45.1  
DOE - Energy Policy Act 1992

### KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

### Available Colors/Finishes



*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	Biscuit
	7	Black Black™



# Wellworth® Classic

Two-piece elongated toilet, 1.6 gpf  
K-3505



## Technical Information

All product dimensions are nominal.

Toilet type:	Floor-mount
Waste Outlet:	Floor
Bowl shape:	Elongated
Flush type:	Pressure Lite
Trap passageway:	2-1/4" (57 mm)
Water surface size:	12" x 10" (305 mm x 254 mm)
Rim to water surface:	5-5/8" (143 mm)
Rough-in:	12" (305 mm)
Seat-mounting holes:	5-1/2" (140 mm)

## Fixture Supply Requirements

Min static pressure:	20 psi (137.9 kPa)
Max static pressure:	80 psi (551.6 kPa)

## Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.