

## Inverter Driven Heat Pump

15,000 BTU Wall Mount Type

Job Name \_\_\_\_\_  
Location \_\_\_\_\_  
Engineer \_\_\_\_\_  
Submitted To \_\_\_\_\_  
Submitted By \_\_\_\_\_  
Reference \_\_\_\_\_

Date \_\_\_\_\_  
Approval \_\_\_\_\_  
Construction \_\_\_\_\_  
Unit No \_\_\_\_\_  
Drawing No \_\_\_\_\_

### PRODUCT FEATURES

Wireless remote controller  
Auto|Cool|Dry|Fan|Heat modes  
24 Hr. timer  
Powerful mode  
Cold prevention  
Auto Restart



MODEL NUMBERS				
Indoor Unit			ASU15RLF1	
Nominal Capacity			15,000	
LINESET REQUIREMENTS				
Connection Method			Flare	
Liquid	in (mm)		Ø 1/4 (Ø 6.35)	
Gas			Ø 1/2 (Ø 12.70)	
Drain hose	Material	PP+HDPE		
	in	Ø 9/16(I.D.), Ø 5/8 to Ø 11/16(O.D.)		
	mm	Ø 13.8(I.D.), Ø 15.8 to Ø 16.7(O.D.)		
INDOOR DIMENSIONS & WEIGHT				
Net (H × W × D)	in (mm)	10-9/16 × 33-1/16 × 8 (268 × 840 × 203)		
Gross (H × W × D)		10-5/8 × 34-13/16 × 14-3/4 (270 × 884 × 336)		
Net Weight	lb (kg)	19 (8.5)		
Gross Weight		23 (10.5)		
ELECTRICAL SPECIFICATIONS				
Voltage/Frequency/Phase			208/230 V ~ 60 Hz	
Available Voltage Range			187–253 V	
Running Current		A	0.25	
Input Power		W	28	
SOUND PRESSURE				
Indoor Unit	Cooling	HIGH	dB (A)	42
		MED		38
		LOW		33
		QUIET		25
	Heating	HIGH		42
		MED		38
		LOW		35
		QUIET		27
FAN DATA				
Indoor Unit Airflow rate	Cooling	HIGH	CFM (m3/h)	430 (730)
		MED		353 (600)
		LOW		312 (530)
		QUIET		212 (360)
	Heating	HIGH		430 (730)
		MED		362 (615)
		LOW		330 (560)
		QUIET		221 (375)

### Warranty Information



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence, and installed by a Fujitsu Elite contractor

### ENCLOSURE

Enclosure	Material	Polystyrene
	Color	White

### ACCESSORIES

UTY-TTRXZ1	24V Thermostat Interface
UTY-XCBXZ2	Interface Kit
UTY-RNNUM	Wired Remote
UTY-RVNUM	Wired Remote w/backlight
UTY-RSNUM	Simple Remote
UTY-XWZXZ5	Dry Contact Wire Kit
FJ-RC-WIFI-1NA	Intesis Wired WiFi module
FJ-IR-WIFI-1NA	Intesis IR WiFi module
UTY-TFNXZ2	WiFi Interface Module

Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation  
<https://connect.fujitsugeneral.com>


Effective Date: 1/10/2023

Fujitsu General America, Inc. • 340 Changebridge Rd, Pine Brook, NJ 07058 • Toll Free: (888) 888-3424 • [www.fujitsugeneral.com](http://www.fujitsugeneral.com)


DIMENSIONS:

Wall Bracket Data:

Units: In. (mm)



Indoor Unit:



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Airstage logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2022 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:  
Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit – indoor unit).