

FJ-RC-WIFI-1BT
3-Wire Remote Controller WiFi Adapter

Job Name _____
 Location _____
 Engineer _____
 Submitted To _____
 Submitted By _____
 Reference _____

Date _____
 Approval _____
 Construction _____
 Unit No _____
 Drawing No _____

MODEL NUMBER:
FJ-RC-WIFI-1BT

GENERAL INFO

Intesis AC Cloud Control interface for 3-wire remote controller-compatible Halcyon indoor units

GENERAL FEATURES

- A plug-in interface which connects your Halcyon indoor unit to the Intesis AC Cloud Control app
- Connects wirelessly to your router using the 2.4GHz WiFi band
- Bluetooth connection (for registration)
- Includes operational control, monitoring, and scheduling for commonly used functions, including:
 - Equipment start/stop, operation mode, and fan control
 - Room temperature (when used with wired remote controller)
 - Error code reporting
 - Filter status and reset
- Over-the-air (OTA) software updates
- Offers simultaneous control of the indoor unit by a Fujitsu remote controller and the app
- Works with Google Home and Amazon Alexa
- Small form factor, can be mounted on the wall or above ceiling
- 2 year manufacturer's warranty

ELECTRICAL

Power Supply, Consumption	12Vdc, 55mA
Source	Indoor unit through RC interface
RF frequency range	2412 to 2484 MHz
Output power (average):	20 dBm (11Mb/Sec.) 14 dBm (72.2Mb/Sec.)

EQUIPMENT CONNECTIONS

Device to IDU	3-cond cable, #18-22AWG stranded
---------------	----------------------------------

OPERATING ENVIRONMENT

Operating Temperature Range °F (°C)	32-104°F (0-40°C)
Operating humidity	<93% RH, no condensation
Stock humidity	<93% RH, no condensation
RoHS conformity	Compliant with RoHS directive (2011/65/EU)

WEIGHT AND DIMENSIONS

Net weight oz. (g)	2.8 (80)
H x W x D inches (mm)	4.25 x 2.75 x 1.13 (108 x 70 x 28)

COMPATIBLE WIRED REMOTE CONTROLLERS

UTY-RNKU, UTY-RSKU, UTY-RHKU

ORDERING CODE

FJ-RC-WIFI-1BT

COMPATIBLE INDOOR UNITS

ABU18RULX	ARU7RLF	ASU7RLF1 ¹
ABU24RULX	ARU9RLF	ASU9RLF1 ¹
ABU36RSLX	ASU12RLF1 ¹	AUU12RLF
AGU12RLF	ASU15RLF1 ¹	AUU18RLF
AGU15RLF	ASU18RLB ²	AUU7RLF
AGU9RLF	ASU18RLF ²	AUU9RLF
ARU12RLF	ASU24RLB ²	
ARU18RLF	ASU24RLF ²	
ARU24RLF	ASU30RLXB ²	

¹ Requires interface kit UTY-XCBX22 and wiring kit UTY-WIFI.

² Requires wiring kit UTY-WIFI.

Due to continuous product improvements, specifications are subject to change without notice. Please log in to Fujitsu Connect for the most up-to-date documentation (<https://connect.fujitsugeneral.com>)


Effective Date: 6/6/2022

Ver.: FJ-RC-WIFI-1BT :2022A

Fujitsu General America, Inc. • 340 Changebridge Rd, Pine Brook, NJ 07058 • Toll Free: (888) 888-3424 • www.fujitsugeneral.com

DIMENSIONS

Unit: in (mm)



CONNECTION

