



A CSW Industrials Company

PRODUCT DATA SHEET

K.O. DIRT BLASTER™ *High Pressure Pro* Dirt and grease stripper



Description

K.O. DIRT BLASTER™ *High Pressure Pro* is a high-pressure cleaner and degreaser for small condenser coils in restaurant and food service refrigeration, air conditioning, and other machine parts. K.O. Dirt Blaster™ *High Pressure Pro* strips off dirt and cooking grease without a water rinse. It contains a quick-drying solvent and has a pleasant citrus scent.

Application

K.O. Dirt Blaster™ *High Pressure Pro* quickly dissolves grease and oil on refrigeration coils, oil burner surfaces, and other machine parts. It is particularly effective on restaurant grease and other greasy surfaces.

Characteristics | Features

- Dissolves grease and oil quickly
- Pressure washes small condenser coils without a water rinse
- Quick drying/Pleasant citrus scent
- No CFCs
- Meets all EPA and state VOC regulations
- New non-chlorinated formulation

Packaging

| Code | Size | Qty per Case | Lbs. per Case | Cubic Ft per Case |
|-------|--------------------|--------------|---------------|-------------------|
| 88440 | 12.2 ounce aerosol | 12 | 19 | 0.52 |

DANGER! NOT FOR USE ON ENERGIZED ELECTRICAL EQUIPMENT.

Instructions

READ ALL DIRECTIONS, SDS, AND WARNINGS ON LABEL BEFORE USING.
DO NOT USE ON HOT SURFACES, PLASTICS, OR PAINT WITHOUT TESTING FIRST.
USE ONLY IN WELL-VENTILATED AREAS.

FOR USE ON CONDENSER COILS

1. Shut off and de-energize all equipment.
2. Place cardboard behind coil before spraying through coil fins to prevent any loosened debris from dripping or staining other surfaces.
3. Saturate condenser coil with K.O. Dirt Blaster™ *High Pressure Pro*.
4. Wait until all liquid solvent has evaporated and all vapor (odors) are gone before starting up equipment.
5. Although K.O. Dirt Blaster™ *High Pressure Pro* needs no rinsing or wiping, water pressure may be used to float out debris.

FOR USE ON OIL BURNER AND ALL OTHER EQUIPMENT

Use only on cool surfaces. Extinguish all flames, including pilot lights, and turn off stoves, ovens, heaters, electric motors, and other sources of ignition during use.

1. Spray on. The heavier the dirt and grease layer, the heavier the required amount of spray.
2. For heavy films and tars, allow 5 minutes soaking time, then wipe or flush off.
3. Wait until all liquid solvent has evaporated and all vapors (odors) are gone before starting up equipment.

For additional technical information, call Toll Free 1-800-231-3345

DANGER!

Extremely flammable aerosol.
Contains gas under pressure;
May explode if heated.
Causes serious eye irritation.
May cause drowsiness or dizziness.

For additional information, refer to Safety Data Sheet.

K.O. DIRT BLASTER™

High Pressure Pro
Dirt and grease stripper

Precautions

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300 OR AUSTRALIA +(61)-290372994

KEEP OUT OF REACH OF CHILDREN.

For additional information, refer to Safety Data Sheet.

Specifications

| | |
|---------------------|-----------------|
| Flash Point SETA CC | 1 °F (-17 °C) |
| Color | Colorless |
| Shelf Life | 2 years minimum |

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

Limited Warranty



For more information on our product warranty, visit RectorSeal.com

Manufactured for

RectorSeal, LLC

2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

PO Box 5266, Brendale, Qld 4500, Australia • 1300 772 878 • rectorseal.com.au

3255 Wyandotte St. East, Windsor, ON N8Y 1E9, Canada • 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2025 RectorSeal. All rights reserved. R50192-0325