

Window Units - Remote with Electric Heat

1 yr

FEATURES

- Multiple Functions - Cooling, Dehumidifying & Fan Ventilation
- Installation Kit with Expandable Side Panels
- Retracting Louvers



Electrical Requirements



NEMA 5-15A
115 VOLT
15 AMP



NEMA 6 - 15P
230 VOLT
15 AMP



NEMA 6 - 20P
230 VOLT
20 AMP



NEMA 6 - 30P
230 VOLT
25 AMP



NEW

| | While Supplies Last | Replaces WH48YRB | | | |
|------------------------------------|----------------------|----------------------|-----------------|-----------------|---------------|
| Model Number | WH48YRB | WH48YRC | WH412ZRB | WH418ZRC | WH425ZRC |
| Product Code | 422-0115 | 422-0134 | 422-0116 | 422-0129 | 422-0130 |
| BTU Cooling | 8,000 | 8,000 | 11,600 / 12,000 | 18,200 / 18,500 | 24,700/25,000 |
| BTU Heating | 3,500 | 3,500 | 8,500/11,000 | 13,000 / 16,000 | 13,000/16,300 |
| EER | 10.9 | 10.9 | 10.9 | 10.7 | 9.4 |
| Dehumidification (pints/hour) | 1.6 | 1.6 | 2.5 | 3.8 | 6.3 |
| Airflow (CFM) | 593 / 520 / 441 | 642 / 563 / 482 | 696 / 633 / 553 | 446/388/329 | 523/485/445 |
| Voltage | 115 | 115 | 208 / 230 | 208 / 230 | 208 / 230 |
| Frequency / Cycle | 60 HZ | 60 HZ | 60 HZ | 60 HZ | 60 HZ |
| Amps Cooling | 6.3 | 6.4 | 5.2 / 5.0 | 8.3 / 7.7 | 12.4 / 11.3 |
| Amps Heating | 11.6 | 11.7 | 14.5/16 | | |
| Watts Cooling | 734 | 734 | 1064 / 1100 | 1701/1729 | 2628/2660 |
| Watts Heating | 1220 | 1220 | 2821/3450 | 4160/5060 | 4200/5100 |
| Plug Type / Nema # | 5-15A | 5-15P | 6-20P | 6-30P | 6-30P |
| Power Cord Rating/ amps | 15 | 15 | 20 | 30 | 30 |
| Power Cord Type | LCDI | LCDI | LCDI | LCDI | LCDI |
| Power Cord Length | 76 | 96 | 69 | 78 | 84 |
| Refrigerant | R410A | R410A | R410A | R410A | R410A |
| Refrigerant Charge/ Oz. | 13.4 | 13.4 | 22.22 | 28.92 | 34.22 |
| Sound (Indoor/Outdoor) dba | 57.5 / 64.5 | 57.2 / 64.3 | 60.9 / 67.2 | 60/66 | 63.2/68.2 |
| 4 Way Air Adjustment | Yes | Yes | Yes | YES | YES |
| 2 Way Air Swing | Yes | Yes | Yes | YES | YES |
| Air Discharge | Top Front | Top Front | Top Front | Top Front | Top Front |
| Motor Type | Ball bearing | Ball bearing | Ball bearing | Ball Bearing | Ball Bearing |
| Motor Capacitor / mfd | 50 + 15µF(Dual Type) | 45 + 15µF(Dual Type) | 4µF | 8µF | 8µF |
| Controls | Remote | Remote | Remote | Remote | Remote |
| Operating Range | 64 - 109 °F | 64 - 109 °F | 64 - 109 °F | 64 - 109 °F | 64 - 109 °F |
| Cabinet Size/ inches | | | | | |
| Width | 22.6" | 22.6" | 22.6" | 23.6" | 26.5" |
| Depth | 23" | 23" | 23" | 25.4" | 26.5" |
| Height | 16.1" | 16.1" | 16.1" | 17.9" | 18.6" |
| Window Opening Width (min / max) | 26.8" - 36" | 26.8" - 36" | 26.8" - 36" | 26.5 - 40.5" | 31 - 42" |
| Thru. Wall Max. Thickness (Inches) | 6.1" | 6.1" | 6.1" | 8" | 10" |
| N.W. / G.W lbs. | 70.6 / 82 | 75.8 / 87.3 | 83.8 / 94.8 | 118.4/133.4 | 136.5/155.6 |
| Approvals | cULus | cULus | cULus | cULus | cULus |
| Chassis Slide Out | Yes | Yes | Yes | Yes | Yes |