



Submittal Data Sheet

2.5 Ton, Cased With Internal TXV Upflow/Downflow, Coil
CAPT3131B4

STANDARD FEATURES

- All-Aluminum evaporator coil
- Optimized for use with R-410A refrigerant
- Some models suitable for use with R-410A or R-22 refrigerant
- CAPT models feature factory-installed thermal expansion valves for cooling and heat pump applications
- Check flowrator for cooling and heat pump applications
- Vertical and horizontal models available
- 21" depth for easier attic access
- Split seam front for easy access
- Foil-faced insulation covers the internal casing to reduce cabinet condensation
- Galvanized, leather grain-embossed finish
- Rust resistant, thermoplastic drain pans featuring a low water-retention design
- DecaBDE-free thermoplastic drain pan with secondary drain connections
- UV-resistant drain pan
- AHRI certified
- ETL listed





Submittal Data Sheet

2.5 Ton, Cased With Internal TXV Upflow/Downflow, Coil
CAPT3131B4

PERFORMANCE

Product Model No.	CAPT3131B4	Product Model Name:	2.5 Ton, Cased With Internal TXV Upflow/Downflow, Coil
Type:	Coil	Cooling Capacity (Nominal) (Btu/hr):	30,000

PRODUCT DETAILS

Dimensions (HxWxD) (in):	22 x 17-1/2 x 21	Suction Valve Connection Size (inch):	3/4
Net Weight (lb):	46	Liquid Valve Connection Size (inch):	3/8
Gross Weight (lb):	46	Condensate Connection (inch):	3/4

Submittal Data Sheet

2.5 Ton, Cased With Internal TXV Upflow/Downflow, Coil

CAPT3131B4

DIMENSIONAL DRAWING

MODEL	CABINET DIMENSIONS			NOMINAL TONS	CONNECTION		SHIP WEIGHT (LBS)
	W	D	H		LIQUID	SUCTION	
CAPT3131B4	17½"	21"	22"	2½	⅜"	¾"	46
CAPT3131C4	21"	21"	22"	2½	⅜"	¾"	50
CAPT3743C4	21"	21"	30"	3-3½	⅜"	⅞"	63
CAPT3743D4	24½"	21"	30"	3-3½	⅜"	⅞"	75
CAPT4961C4	21"	21"	30"	4-5	⅜"	⅞"	73
CAPT4961D4	24½"	21"	30"	4-5	⅜"	⅞"	76

DIMENSIONS

