

Job Name:	
Tag#	



## Submittal Data Sheet

3MXS24RMVJUA

3 Port, 2-Ton Outdoor Heat Pump



Complete warranty details available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com). To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. *If product is installed in a commercial application, limited warranty period is 5 years.*

### Outdoor Specifications

Compressor	Hermetically Sealed Swing Type			
Refrigerant	R-410A			
Factory Charge (Lbs)	6.17			
Refrigerant Oil	PVE (FVC50K)			
Airflow Rate (cfm)	Cooling		Heating	
	H	2,094	H	2,094
	M	2,094	M	1,981
	L	1,981	L	1,119
Sound Power Level (dBA)	52 / 54			
Dimensions (H x W x D) (in)	28-15/16 x 34-1/4 x 12-5/8			
Weight (Lbs)	137			

### Efficiency

	SEER	EER	HSPF	COP
Non-Ducted	18	12.7	12.5	3.53
Ducted	14	9.7	8.2	3.44
Mixed	16	11.2	10.35	3.49

### Performance

Cooling (Btu/hr)	
Rated	24,000
Operating Range	14°F – 115°F

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB  
Outdoor: 95°F DB/75°F WB

Heating (Btu/hr)	
Rated	24,000
Operating Range	5°F – 60°F

Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 47°F DB/43°F WB

### Electrical

	208/60/1	230/60/1
System MCA	21.9	21.9
System MFA	25	25
Compressor RLA	15.5	15.5
Outdoor fan motor FLA	.25	25
Outdoor fan motor W	73	73

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)  
RLA: Rated load amps (A) W: Fan motor rated output (W)


### Piping

Liquid (in)	¼ x 3
Gas (in)	3/8 x 1, ½ x 2
Drain (in)	11/16
Max. System Piping Length (ft)	230
Max. Interunit Piping Length (ft)	82
Max. Height Difference – IDU to ODU (ft)	49.25
Max. Height Difference – IDU to IDU (ft)	24.625
Chargeless (ft)	131.6
Additional Charge of Refrigerant (oz/ft)	.21

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

# 3MXS24RMVJUA Dimensional Data



C: 3D093198

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: June 2022

Page 2 of 7

## Optional Accessories



Included	Part Number	Description
	DACA-WB-3	Mounting Bracket
	KEH063A4EA	Drain Pan Heater 2/3/4MXS & 2/3MXL
	KPW063B4	Air Adjustment Grille
	KKG063A42	Back protection wire net
	KKG063A43	Side protection wire net
	KPS063A41	Snow hood (intake side plate)
	KPS063A44	Snow hood (intake rear plate)
	KPS063A47	Snow hood (outlet)

# 3MXS24RMVJUA Capacity Tables



## Non- Ducted, 60 Hz, 208-230V

Combination of indoor unit	Cooling Capacity of each indoor unit				Heating Capacity of each indoor unit	
	Each Capacity				Total Indoor Unit Capacity	
	A room	B room	C room	D room	Rating	(min ~ max)
07	7.60	—	—	—	7.60	7.30 ~ 8.40
	8.80	—	—	—	8.80	8.70 ~ 9.70
09	9.80	—	—	—	9.80	7.40 ~ 10.80
	11.30	—	—	—	11.30	10.00 ~ 12.50
12	13.00	—	—	—	13.00	7.50 ~ 14.40
	15.00	—	—	—	15.00	9.90 ~ 16.70
15	16.30	—	—	—	16.30	8.90 ~ 18.00
	18.80	—	—	—	18.80	9.40 ~ 20.80
18	19.50	—	—	—	19.50	8.90 ~ 21.60
	22.50	—	—	—	22.50	9.40 ~ 25.00
07+07	7.60	7.60	—	—	15.20	8.90 ~ 16.80
	8.75	8.75	—	—	17.50	9.30 ~ 19.40
07+09	7.69	9.61	—	—	17.30	8.90 ~ 19.20
	8.89	11.11	—	—	20.00	9.20 ~ 22.20
07+12	7.31	12.79	—	—	20.10	9.00 ~ 22.80
	8.25	14.45	—	—	22.70	9.10 ~ 26.60
07+15	6.31	15.79	—	—	22.10	10.00 ~ 26.40
	6.69	16.71	—	—	23.40	8.70 ~ 31.30
07+18	6.00	18.00	—	—	24.00	10.10 ~ 30.00
	6.00	18.00	—	—	24.00	8.70 ~ 36.00
09+09	9.75	9.75	—	—	19.50	9.00 ~ 21.60
	11.25	11.25	—	—	22.50	9.10 ~ 25.00
09+12	8.92	12.48	—	—	21.40	9.10 ~ 25.20
	9.63	13.48	—	—	23.10	9.00 ~ 29.70
09+15	7.80	15.60	—	—	23.40	10.10 ~ 28.80
	7.93	15.87	—	—	23.80	9.70 ~ 34.40
09+18	7.06	16.94	—	—	24.00	10.10 ~ 30.00
	7.06	16.94	—	—	24.00	8.60 ~ 36.00
12+12	11.70	11.70	—	—	23.40	9.20 ~ 28.80
	11.90	11.90	—	—	23.80	9.00 ~ 34.40
12+15	9.88	14.12	—	—	24.00	10.20 ~ 30.00
	9.88	14.12	—	—	24.00	8.60 ~ 36.00
12+18	8.84	15.16	—	—	24.00	10.20 ~ 30.00
	8.84	15.16	—	—	24.00	8.60 ~ 36.00
15+15	12.00	12.00	—	—	24.00	10.80 ~ 30.00
	12.00	12.00	—	—	24.00	8.40 ~ 36.00
15+18	10.91	13.09	—	—	24.00	10.80 ~ 30.00
	10.91	13.09	—	—	24.00	8.40 ~ 36.00
18+18	12.00	12.00	—	—	24.00	10.90 ~ 30.00
	12.00	12.00	—	—	24.00	8.30 ~ 36.00
07+07+07	7.13	7.13	7.13	—	21.40	10.00 ~ 25.20
	7.70	7.70	7.70	—	23.10	8.60 ~ 29.70
07+07+09	6.98	6.98	8.73	—	22.70	10.10 ~ 27.60
	7.26	7.26	9.08	—	23.60	8.60 ~ 32.90
07+07+12	6.40	6.40	11.19	—	24.00	10.10 ~ 30.00
	6.40	6.40	11.20	—	24.00	8.50 ~ 36.00
07+07+15	5.33	5.33	13.33	—	24.00	10.80 ~ 30.00
	5.33	5.33	13.32	—	24.00	8.30 ~ 36.00
07+07+18	4.80	4.80	14.40	—	24.00	10.80 ~ 30.00
	4.80	4.80	14.40	—	24.00	8.30 ~ 36.00
07+09+09	6.86	8.57	8.57	—	24.00	10.10 ~ 30.00
	6.85	8.57	8.57	—	24.00	8.50 ~ 36.00
07+09+12	6.00	7.50	10.49	—	24.00	10.20 ~ 30.00
	6.00	7.50	10.50	—	24.00	8.50 ~ 36.00
07+09+15	5.05	6.32	12.63	—	24.00	10.90 ~ 30.00
	5.05	6.32	12.63	—	24.00	8.30 ~ 36.00
07+09+18	4.57	5.71	13.71	—	24.00	10.90 ~ 30.00
	4.57	5.71	13.71	—	24.00	8.30 ~ 36.00

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

# 3MXS24RMVJUA Capacity Tables



Combination of indoor unit	Cooling Capacity of each indoor unit					
	Heating Capacity of each indoor unit					
	Each Capacity				Total Indoor Unit Capacity	
	A room	B room	C room	D room	Rating	(min ~ max)
07+12+12	5.33	9.33	9.33	—	24.00	10.30 ~ 30.00
	5.34	9.33	9.33	—	24.00	8.40 ~ 36.00
07+12+15	4.57	8.00	11.43	—	24.00	10.90 ~ 30.00
	4.57	8.00	11.42	—	24.00	8.30 ~ 36.00
07+12+18	4.17	7.30	12.52	—	24.00	10.90 ~ 30.00
	4.17	7.30	12.52	—	24.00	8.30 ~ 36.00
07+15+15	4.01	10.00	10.00	—	24.00	11.20 ~ 30.00
	3.99	10.00	10.00	—	24.00	8.20 ~ 36.00
09+09+09	8.00	8.00	8.00	—	24.00	10.20 ~ 30.00
	8.00	8.00	8.00	—	24.00	8.50 ~ 36.00
09+09+12	7.06	7.06	9.89	—	24.00	10.30 ~ 30.00
	7.06	7.06	9.88	—	24.00	8.40 ~ 36.00
09+09+15	6.00	6.00	12.00	—	24.00	10.90 ~ 30.00
	6.00	6.00	11.99	—	24.00	8.30 ~ 36.00
09+09+18	5.45	5.45	13.10	—	24.00	10.90 ~ 30.00
	5.45	5.45	13.08	—	24.00	8.30 ~ 36.00
09+12+12	6.32	8.84	8.84	—	24.00	10.30 ~ 30.00
	6.31	8.84	8.84	—	24.00	8.40 ~ 36.00
09+12+15	5.45	7.64	10.91	—	24.00	10.90 ~ 30.00
	5.45	7.64	10.91	—	24.00	8.20 ~ 36.00
09+12+18	5.00	7.00	12.00	—	24.00	10.90 ~ 30.00
	5.00	7.00	12.00	—	24.00	8.20 ~ 36.00
09+15+15	4.80	9.60	9.60	—	24.00	11.20 ~ 30.00
	4.80	9.60	9.60	—	24.00	8.20 ~ 36.00
12+12+12	8.00	8.00	8.00	—	24.00	10.40 ~ 30.00
	8.00	8.00	8.00	—	24.00	8.40 ~ 36.00
12+12+15	7.00	7.00	10.01	—	24.00	11.00 ~ 30.00
	7.00	7.00	10.00	—	24.00	8.20 ~ 36.00

# 3MXS24RMVJUA Capacity Tables



## Ducted, 60 Hz, 208-230V

Combination of indoor unit	Cooling Capacity of each indoor unit				Heating Capacity of each indoor unit	
	Each Capacity				Total Indoor Unit Capacity	
	A room	B room	C room	D room	Rating	(min ~ max)
7	7.1	—	—	—	7.1	7.30 - 7.10
	8.3	—	—	—	8.3	9.00 - 9.70
09	9.1	—	—	—	9.1	7.30 - 9.60
	10.7	—	—	—	10.7	10.40 - 12.50
12	12.1	—	—	—	12.1	7.30 - 12.10
	14.3	—	—	—	14.3	10.40 - 16.70
15	14.8	—	—	—	14.8	8.10 - 15.40
	16.6	—	—	—	16.6	10.10 - 20.80
18	17.6	—	—	—	17.6	8.10 - 18.80
	18.9	—	—	—	18.9	10.10 - 25.00
07+07	6.95	6.95	—	—	13.9	8.80 - 14.30
	7.9	7.9	—	—	15.8	9.60 - 19.40
07+09	7.02	8.78	—	—	15.8	8.80 - 16.60
	7.73	9.67	—	—	17.4	9.60 - 22.20
07+12	6.73	11.77	—	—	18.5	8.80 - 19.90
	7.13	12.47	—	—	19.6	9.60 - 25.90
07+15	6.09	15.21	—	—	21.3	9.40 - 23.30
	6.23	15.57	—	—	21.8	9.40 - 28.40
07+18	6	18	—	—	24	9.40 - 26.60
	6	17.99	—	—	24	9.40 - 31.00
09+09	8.8	8.8	—	—	17.6	8.80 - 18.80
	11.05	11.05	—	—	22.1	9.60 - 25.00
09+12	8.45	11.84	—	—	20.3	8.80 - 22.10
	8.79	12.3	—	—	21.1	9.60 - 27.60
09+15	7.7	15.4	—	—	23.1	9.40 - 25.50
	7.77	15.53	—	—	23.3	9.40 - 30.10
09+18	7.06	16.94	—	—	24	9.40 - 27.00
	7.06	16.94	—	—	24	9.40 - 32.00
12+12	11.55	11.55	—	—	23.1	8.80 - 25.50
	11.65	11.65	—	—	23.3	9.60 - 30.10
12+15	9.88	14.12	—	—	24	9.40 - 27.00
	9.88	14.12	—	—	24	9.40 - 32.00
12+18	8.84	15.16	—	—	24	9.40 - 27.00
	8.84	15.16	—	—	24	9.40 - 32.00
15+15	12	12	—	—	24	9.90 - 27.00
	12	12	—	—	24	9.10 - 32.00
15+18	10.91	13.09	—	—	24	9.90 - 27.00
	10.91	13.09	—	—	24	9.10 - 32.00
18+18	12	12	—	—	24	9.90 - 27.00
	12	12	—	—	24	9.10 - 32.00
07+07+07	6.77	6.77	6.77	—	20.3	9.90 - 22.10
	7.03	7.03	7.03	—	21.1	9.00 - 27.60
07+07+09	6.83	6.83	8.54	—	22.2	9.90 - 24.40
	6.92	6.92	8.65	—	22.5	9.00 - 29.30
07+07+12	6.4	6.4	11.19	—	24	9.90 - 26.60
	6.4	6.4	11.19	—	24	9.00 - 31.10
07+07+15	5.33	5.33	13.33	—	24	10.40 - 26.70
	5.33	5.33	13.32	—	24	8.80 - 31.40
07+07+18	4.8	4.8	14.4	—	24	10.40 - 26.90
	4.8	4.8	14.4	—	24	8.80 - 31.60
07+09+09	6.86	8.57	8.57	—	24	9.90 - 26.60
	6.86	8.57	8.57	—	24	9.00 - 31.00
07+09+12	6	7.5	10.5	—	24	9.90 - 26.70
	6	7.5	10.5	—	24	9.00 - 31.30

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

# 3MXS24RMVJUA Capacity Tables



Combination of indoor unit	Cooling Capacity of each indoor unit					
	Heating Capacity of each indoor unit					
	Each Capacity				Total Indoor Unit Capacity	
	A room	B room	C room	D room	Rating	(min ~ max)
07+09+15	5.05	6.32	12.63	—	24	10.40 - 26.80
	5.05	6.32	12.63	—	24	8.80 - 31.50
07+09+18	4.57	5.71	13.71	—	24	10.40 - 26.90
	4.57	5.71	13.7	—	24	8.80 - 31.80
07+12+12	5.33	9.33	9.33	—	24	9.90 - 26.80
	5.32	9.33	9.33	—	24	9.00 - 31.50
07+12+15	4.57	8	11.43	—	24	10.40 - 26.90
	4.57	8	11.43	—	24	8.80 - 31.80
07+12+18	4.17	7.3	12.53	—	24	10.40 - 27.00
	4.17	7.3	12.51	—	24	8.80 - 32.10
07+15+15	4.01	10	10	—	24	10.70 - 27.00
	4	10	10	—	24	8.60 - 32.10
09+09+09	8	8	8	—	24	9.90 - 27.00
	8	8	8	—	24	9.00 - 32.00
09+09+12	7.06	7.06	9.88	—	24	9.90 - 27.00
	7.06	7.06	9.87	—	24	9.00 - 32.00
09+09+15	6	6	12	—	24	10.40 - 27.00
	6	6	12	—	24	8.80 - 32.00
09+09+18	5.45	5.45	13.1	—	24	10.40 - 27.00
	5.45	5.45	13.09	—	24	8.80 - 32.00
09+12+12	6.32	8.84	8.84	—	24	9.90 - 27.00
	6.33	8.84	8.84	—	24	9.00 - 32.00
09+12+15	5.45	7.64	10.91	—	24.00	10.40 ~ 27.00
	5.45	7.64	10.91	—	24	8.80 - 32.00
09+12+18	5.00	7.00	12.00	—	24.00	10.40 ~ 27.00
	5	7	12	—	24	8.80 - 32.30
09+15+15	4.80	9.60	9.60	—	24.00	10.70 ~ 27.00
	4.8	9.6	9.6	—	24	8.60 - 32.30
12+12+12	8.00	8.00	8.00	—	24.00	9.90 ~ 27.00
	8	8	8	—	24	9.00 - 32.00
12+12+15	7.00	7.00	10.00	—	24.00	10.40 ~ 27.00
	7	7	10	—	24	8.80 - 32.30