



Submittal Data Sheet

1.25-Ton Ceiling Mounted Cassette and Heat Pump

FFQ15W2VJU9RX15WMVJU9

Model		Indoor Unit		FFQ15W2VJU9	
		Outdoor Unit		RX15WMVJU9	
				Cooling	Heating
Power Supply				1 ϕ , 208 - 230 V, 60 Hz	
Capacity Rated (Min. - Max.)			Btu/h	14,400 (5,100 - 16,200)	16,200 (5,200 - 16,300)
Running Current (Rated)			A	6.34 - 5.73	6.80 - 6.15
Power Consumption (Rated)			W	1,252 - 1,252	1,349 - 1,349
Power Factor (Rated)			%	94.9 - 95.0	95.4 - 95.4
SEER2 / HSPF2				19.60	8.80
EER2 (Rated)			Btu/h·W	11.50	—
COP2 (Rated)			W/W	—	3.52
Piping Connections	Liquid	in. (mm)	ϕ 1/4 (6.4)		
	Gas	in. (mm)	ϕ 1/2 (12.7)		
	Drain	in. (mm)	VP20 (O.D. ϕ 1-1/32 (26))		
Heat Insulation				Both Liquid and Gas Pipes	
Max. Interunit Piping Length			ft (m)	98-1/2 (30)	
Max. Interunit Height Difference			ft (m)	65-5/8 (20)	
Chargeless			ft (m)	32-3/4 (10)	
Amount of Additional Charge of Refrigerant			oz/ft (g/m)	0.21 (20)	
Indoor Unit				FFQ15W2VJU9	
Decoration Panel (1)	Model (Color)		BYFQ60B3W1 (White)		
	Dimensions (H \times W \times D)	in. (mm)	2-3/16 \times 27-9/16 \times 27-9/16 (55 \times 700 \times 700)		
	Weight (Mass)	lbs (kg)	6.0 (2.7)		
Decoration Panel (2)	Model (Color)		BYFQ60C2W1W (White) / BYFQ60C2W1S (Silver)		
	Dimensions (H \times W \times D)	in. (mm)	1-13/16 \times 24-7/16 \times 24-7/16 (46 \times 620 \times 620)		
	Weight (Mass)	lbs (kg)	6.2 (2.8)		
Heat Exchanger	Rows \times Stages, Fin per Inch		2 \times 16, 21		
	Fin Spec / Tube		Slit Fin / ϕ 5 Hi-XA Tube		
Airflow Rate	H / M / L	cfm	420 / 367 / 293		441 / 385 / 307
		m3/min	11.9 / 10.4 / 8.3		12.5 / 10.9 / 8.7
Fan	Type / Speed		Turbo Fan / 3 Steps		
Running Current (Rated)			A	0.29 - 0.26	0.29 - 0.26
Power Consumption (Rated)			W	28 - 28	28 - 28
Power Factor (Rated)			%	46.4 - 46.8	46.4 - 46.8

Daikin Comfort Technologies North America, Inc 19001 Kermier Rd Waller TX 77484
 Daikin City Generated Submittal Data www.daikincomfort.com or www.daikinac.com


(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications, and information in this data sheet without notice and without incurring any obligations)



Submittal Data Sheet
1.25-Ton Ceiling Mounted Cassette and Heat Pump
FFQ15W2VJU9RX15WMVJU9


Temperature Control			Microcomputer Control	
Dimensions (H × W × D)		in. (mm)	10-1/4 × 22-5/8 × 22-5/8 (260 × 575 × 575)	
Weight (Mass)		lbs (kg)	36 (16)	
Sound Pressure Level	H / M / L	dB(A)	40 / 37 / 31	40 / 37 / 31
Remote Controller (Option)		Wired	BRC1E73	
		Wireless	BRC082A41W / BRC082A42W / BRC082A42S	
Outdoor Unit			RX15WMVJU9	
Casing Color			Ivory White	
Heat Exchanger	Fin Spec / Tube		Waffle Fin (PE) / φ 7 Hi-XSL Tube	
Fan Motor	Motor Output	HP	0.10	
Compressor	Type		Hermetically Sealed Swing Type	
	Model		2YC36PXD	
Refrigerant Oil	Type		FVC50K	
	Charge	oz (L)	21.98 (0.650)	
Refrigerant	Type		R-410A	
	Charge	lbs (kg)	2.49 (1.13)	
Airflow Rate		cfm (m3/min)	2,313 (65.5)	2,108 (59.7)
Fan	Type		Propeller	
Running Current (Rated)		A	6.05 - 5.47	6.51 - 5.89
Power Consumption (Rated)		W	1,224 - 1,224	1,321 - 1,321
Power Factor (Rated)		%	97.3 - 97.3	97.6 - 97.5
Dimensions (H × W × D)		in. (mm)	28-15/16 × 34-1/4 × 12-5/8 (735 × 870 × 320)	
Weight (Mass)		lbs (kg)	100 (45)	
Sound Pressure Level		dB(A)	50	51
Conditions Based on	Indoor		80.0°FDB (26.7°CDB) / 67.0°FWB (19.4°CWB)	70.0°FDB (21.1°CDB) / 60.0°FWB (15.6°CWB)
	Outdoor		95.0°FDB (35.0°CDB) / 75.0°FWB (24.0°CWB)	47.0°FDB (8.3°CDB) / 43.0°FWB (6.1°CWB)
	Piping Length		25 ft (7.5 m)	
SL: The quiet fan level of the airflow rate setting.				

FFQ09/12/15/18W2VJU9 with BYFQ60B3W1 (Decoration Panel)



C: 3D106040A


FFQ09/12/15/18W2VJU9 with BYFQ60C2W1W(S) (Decoration Panel)



C: 3D106039A


4.2 Outdoor Unit

RX09/12WMVJU9



3D136777

RX15/18WMVJU9



3D092224D

11. Electric Characteristics

Indoor Unit	Outdoor Unit	Power Supply				Compressor	OFM			IFM		
		Hz - Volts	Voltage Range	MCA	MFA		Hp	W	FLA	Hp	W	FLA
FTXR09WVJUW9 FTXR09WVJUS9	RX09WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	7.6	15	7.5	0.03	20	0.17	0.04	29	0.13
FTXR12WVJUW9 FTXR12WVJUS9	RX12WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	7.7	15	7.5	0.03	20	0.17	0.04	29	0.19
FTXR18WVJUW9 FTXR18WVJUS9	RX18WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	11.0	15	10.8	0.12	93	0.58	0.04	29	0.21
FDMQ09WVJU9	RX09WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	8.0	15	7.5	0.03	20	0.17	0.17	130	0.49
FDMQ12WVJU9	RX12WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	8.1	15	7.5	0.03	20	0.17	0.17	130	0.63
FDMQ15WVJU9	RX15WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	8.6	15	8.0	0.10	75	0.47	0.31	230	0.64
FDMQ18WVJU9	RX18WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	11.6	15	10.8	0.12	93	0.58	0.31	230	0.84
FDMQ24WVJU9	RX24WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	13.1	20	12.0	0.12	93	0.58	0.31	230	1.10
FFQ09W2VJU9	RX09WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	7.8	15	7.5	0.03	20	0.17	0.07	50	0.28
FFQ12W2VJU9	RX12WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	7.8	15	7.5	0.03	20	0.17	0.07	50	0.28
FFQ15W2VJU9	RX15WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	8.3	15	8.0	0.10	75	0.47	0.07	50	0.28
FFQ18W2VJU9	RX18WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	11.0	15	10.8	0.12	93	0.58	0.07	50	0.28

Symbols:

MCA	: Min. circuit amps	(A)
MFA	: Max. fuse amps	(A)
RLA	: Rated load amps	(A)
OFM	: Outdoor fan motor	
IFM	: Indoor fan motor	
FLA	: Full load amps	(A)
W / Hp	: Fan motor rated output	(W, Hp)

Notes:

1. RLA is the max current that comes in cooling operation and heating operation.
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.

C: 3D143137

C: 3D143129