

Vertical Hydronic Fan Coil

STANDARD FEATURES

- J+ Advanced Control
- 2 Line Display for Easier Setup
- High Efficiency EC Integrated Motor/Blower Assembly
- 6-Row Copper/Aluminum Coil
- Sweat-Type Connections
- 24V 50/60hz Transformer
- Slide Out Blower
- Insulated Cabinet
- Float Switch
- Condensate Trap
- Anti-Vibration Foam Strips
- Mold Resistant Primary Drain Pan
- Stainless Steel Primary Drain Pan



	Model	WCS2430JV4MB		WCS3642JV4MB		WCS4860JV4MB	
Capacity	Tons	2	2.5	3	3.5	4	5
	CFM @ 1.2" W.C	440	550	660	850	880	1150
Dimensions	Height	33"					
	Width	24"		33"		43"	
	Length	16 1/8"					
	Ship Weight (lbs)	135		170		210	
Connections	Water Out (Top)	7/8" ODF					
	Water In (Botto)	3/8" ODF					
	Cond Drain (NPT)	3/4"					
	Return Dia.	15"		19"		24"	
Coil	Rows	6					
	Medium	Water/Glycol					
Motor	H.P.	3/4					
	Type	EC					
	Wheel Dia & Width	10/6"					
Electrical Data	Volts*	230/115					
	Ph	1					
	Hz**	50/60					
	F.L.Amps @ 230V	2.8		3.8		5.3	
	F.L. Amps @ 115V	5.6		7.6		10.6	
	QTY						

*Units are shipped standard @230v. Field conversion kit provided for 115v supply voltage

**Unit transformer and motor are capable of 50 or 60hz



260 North Elm St., Westfield, MA 01085
(800) 465-8558 Fax: (413) 564-5815

7555 Tranmere Drive, Mississauga, ONT. L5S 1L4 Canada
(905) 670-5888 Fax: (905) 670-5782

www.spacepak.com

PROJECT: _____ DATE: _____

LOCATION: _____

CUSTOMER: _____

ENGINEER: _____

SUBMITTED BY: _____

FOR: ☐ Reference ☐ Approval ☐ Construction

UNIT DESIGNATION: _____

SCHEDULE NUMBER: _____

SUBMITTAL DATA: WCSP-JV SERIES

Dimensional Data – (Inches)

MODEL	A	B	C	D
WCSP-2430 (V)	24-3/8 [619]	18-1/4 [464]	12-3/16 [310]	6-1/16 [154]
WCSP-3642 (V)	33-3/8 [848]	25-1/2 [648]	16-11/16 [424]	15-1/4 [387]
WCSP-4860 (V)	43-3/8 [1102]	38-7/8 [987]	21-11/16 [551]	21-7/8 [556]

