Job Name:	
Tag#	

Submittal Data Sheet

FVXS15NVJU

1.25-Ton Floor Mounted Indoor Unit

12 YEAR PARTS LIMITED WARRANTY

Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. *If product is installed in a commercial application, limited warranty period is 5 years.*

Indoor Specifications

	Cooling		Heating	
Airflow Rate (cfm)	H	M	H	M
	378	325	417	357
	L	SL	L	SL
	275	233	300	251
Sound (dBA) H / M / L / SL	44 / 40 / 36 / 32		45 / 40 / 36 / 32	
Dimensions (H × W × D) (in)	23-5/8 × 27-9/16 × 8-1/4			
Weight (Lbs)	31			
Nominal Capacity (Btu/hr)	15,000			

*See Outdoor Unit for Rated Capacities

Piping

Liquid (in)	1/4
Gas (in)	1/2
Drain (in)	13/16

Electrical

*208/230V

	Cooling	Heating
Running Current (Rated) (A)	.19/.17*	.21/.19*
Power Consumption (Rated) (W)	27/27*	34/34*

Optional Accessories

Included	Part Number	Description
	BRP072A43	Wireless Interface Adapter (S21 Adapter Included)
	DACA-TS1-1	Daikin ENVi Intelligent Thermostat Kit
	BRC944B2-A08	Wired Remote Controller kit (Adaptor Required)
	BRCW901A08	Wired Remote Controller Cable – 25 ft (Included in above kit)
	BRCW901A03	Wired Remote Controller Cable – 10ft
	KAF968B42	Titanium apatite photocatalytic air-purifying filter WITH frame
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump
	KRP928BB2S	Interface Adaptor for DIII-NET


NOTE) 1. THE MARK (→) SHOWS PIPING DIRECTION
14-9/16 (370mm)
9-1/16 (230mm)
25-3/8 (644mm)
MAIN UNIT FIXING SCREW
9-13/16 (250mm)
15-3/4 (400mm)
11/16 (17mm)
HOLE FOR SPLINT
3-1/4 (82mm)
HOLE FOR PIPING
4-3/4 (120.5mm)
3-9/16 (90mm)
FIXED SCREWS FOR FRONT GRILLE (INSIDE)
26-1/4 (666mm) (HALF CONCEALED)
27-9/16 (700mm)
OPERATION LAMP
TIMER LAMP
SIGNAL RECEIVER
INDOOR UNIT ON/OFF SWITCH (HALF CONCEALED)
AIR OUTLET SELECTION SWITCH (INSIDE)
MODEL NAME LABEL
FIXED SCREWS FOR FRONT PANEL
23-1/16 (585mm) ~ 23-7/16 (595mm)
(WALL HOLE)
26-3/8 (670mm) ~ 27-3/16 (690mm)
(WALL HOLE)
WALL HOLE FOR HALF CONCEALED (FOR MAINTENANCE AND PERFORMANCE)
1-15/16 (50mm) MIN
AIRFLOW
REQUIRED SPACE
2-3/4 (70mm)
(FOR PERFORMANCE)
1-15/16 (50mm) MIN
(FOR MAINTENANCE AND PERFORMANCE)
1-1/2 (38.5mm)
4-1/2 (115mm)
3-3/8 (85mm)
FIXED SCREWS FOR MAIN UNIT
24-13/16 (630mm)
HOLE FOR PIPING
2-3/4 (70mm)
5-7/8 (149mm)
6-5/16 (160mm)
1-3/4 (44mm)
1-1/2 (38.5mm)
2-5/16 (58.5mm)
7-7/16 (189mm)
ARC466A21
WIRELESS REMOTE CONTROLLER
SIGNAL TRANSMITTER
7/8 (21.5mm)
DRAIN HOSE
VP20
I.D. φ13/16 (φ20mm)
O.D. φ1 (φ26mm)
L8-11/16 (220mm)
DRAIN SOCKET
23-5/8 (600mm)
10-1/4 (261mm)
8-5/8 (218.5mm)
2-3/4 (70mm)
3-3/4 (95mm)
8-1/4 (210mm)
3-1/4 (82mm)
4-3/4 (121mm)
5-3/8 (136mm)
6 (152mm)
HOLE FOR SPLINT
HOLE FOR PIPING
11/16 (17mm)
3-9/16 (90mm)
4-3/4 (120.5mm)
23 (584mm)
(HALF CONCEALED)
ROOM TEMP THERMISTOR
TERMINAL BLOCK
WITH EARTH (GROUND) TERMINAL
LIQUID PIPE (φ1/4 (φ6.4mm CuT))
GAS PIPE (φ1/2 (φ12.7mm CuT))
NAME PLATE
RIGHT/LEFT (MANUAL)
UPPER AIR OUTLET
UPWARD AIRFLOW LIMIT [OFF]
LOWER AIR OUTLET
UPWARD AIRFLOW LIMIT [ON]
45°
45°
ADJUSTING THE AIRFLOW DIRECTION
UP/DOWN (AUTOMATIC)
COOL, DRY
HEAT
20°
25°
40°
90°
C: 3D091774A