

MRCOOL

Olympus Multi-Zone Series Ductless Mini-Split Heat Pump A/C

Divine Comfort



works with the
Google Assistant

JUST ASK
amazon alexa

SMART CONTROLLER



Multi-Zone Flexibility
Versatile Installation
Superior Performance

Energy Efficient
7 Year Compressor &
5 Year Parts Warranty

 MRCOOL™
COMFORT MADE SIMPLE

Best Features



Smartphone App



Follow me®



Gold Fin® Condenser



DC Inverter



Multi-zone flexibility



Versatile Installation



Superior Performance



Energy Efficient

Specification

HEAT PUMP CONDENSOR - Outdoor Model		MULTI2-18HP230V1	MULTI3-27HP230V1	MULTI4-36HP230V1	MULTI5-48HP230V1
Max Number of Zones		2	3	4	5
Power Supply	Ph-V-Hz	208-230V/60Hz/1	208-230V/60Hz/1	208-230V/60Hz/1	208-230V/60Hz/1
SEER	A	22.5	23	22.5	22.4
Minimum Circuit (Disconnect)	A	18	25	30	35
Maximum Fuse (Breaker)	A	25	35	45	50
Net Dimension (WxDxH)	inch	33.27 x 14.29 x 27.64	37.24 x 16.14 x 31.89	37.24 x 16.14 x 31.89	37.48 x 16.34 x 52.48
Packing Dimension (WxDxH)	inch	37.99 x 15.55 x 29.72	42.91 x 19.69 x 34.06	42.91 x 19.69 x 34.06	43.11 x 19.49 x 54.53
Net weight	lbs	105.82	149.91	156.53	223.77
Gross Weight	Outdoor	lbs	114.64	160.94	255.07
Outdoor noise level		dB(A)	62.4	63.4	64
WALL MOUNTED - Indoor Model		MULTI2-18HP230V1	MULTI3-27HP230V1	MULTI4-36HP230V1	MULTI5-48HP230V1
Power Supply	Ph-V-Hz	208-230V/60Hz/1	208-230V/60Hz/1	208-230V/60Hz/1	208-230V/60Hz/1
Minimum Circuit (Disconnect)	A	9	9	18	20
Maximum Fuse (Breaker)	A	15	15	25	30
Net Dimension (WxDxH)	inch	32.87 x 7.80 x 11.02	32.87 x 7.80 x 11.02	38.98 x 8.58 x 12.40	46.69 x 10.16 x 13.39
Packing Dimension (WxDxH)	inch	35.83 x 10.63 x 13.98	35.83 x 10.63 x 13.98	41.93 x 11.81 x 15.75	49.80 x 16.53 x 13.39
Net weight	lbs	19.8	19.8	26.9	40.1
Gross Weight	lbs	25.4	25.4	34.8	50.3
Piping Size Liquid side/Gas side	inch	1/4"-3/8"	1/4"-1/2"	1/4"-1/2"	3/8"-5/8"
CEILING CASSETTE - Indoor Model		CASSETTE12HP-230	CASSETTE18HP-230	CASSETTE24HP-230	
Power Supply	Ph-V-Hz	208-230V/60Hz/1	208-230V/60Hz/1	208-230V/60Hz/1	
Minimum Circuit (Disconnect)	A	1.3	1.9	10.3	
Maximum Fuse (Breaker)	A	15	15	17.5	
Net Dimension (WxDxH)	inch	22.44 x 22.44 x 10.24	22.44 x 22.44 x 10.24	33.07 x 33.07 x 8.07	
Packing Dimension (WxDxH)	inch	25.79 x 25.79 x 11.42	25.79 x 25.79 x 11.42	35.43 x 35.43 x 8.54	
Net weight	lbs	35.27	39.68	45.19	
Gross Weight	lbs	41.88	46.3	52.91	
Piping Size Liquid side/Gas side	inch	1/4"-1/2"	1/4"-1/2"	3/8"-5/8"	
CEILING RECESSED - Indoor Model		DUCT-09HP-230	DUCT-12HP-230	DUCT-18HP-230	DUCT-24HP-230
Power Supply	Ph-V-Hz	208-230V/60Hz/1	208-230V/60Hz/1	208-230V/60Hz/1	208-230V/60Hz/1
Minimum Circuit (Disconnect)	A	1.2	1.3	1.9	2.5
Maximum Fuse (Breaker)	A	15	15	15	15
Net Dimension (WxDxH)	inch	27.56 x 25 x 8.27	27.56 x 25 x 8.27	36.22 x 25 x 8.27	36.22 x 25 x 10.63
Packing Dimension (WxDxH)	inch	36.02 x 25.79 x 11.42	36.02 x 25.79 x 11.42	44.68 x 25.79 x 11.42	44.68 x 25.79 x 13.78
Net weight	lbs	39.9	39.9	50.7	57.32
Gross Weight	lbs	50.27	50.27	63.93	68.34
Piping Size Liquid side/Gas side	inch	1/4"-3/8"	1/4"-1/2"	1/4"-1/2"	3/8"-5/8"

Specification - Match-Ups

MULTI2-18HP230V1 (18K) - 2 COMBINATIONS

Two Units

9K + 9K	9K + 12K*
---------	-----------

MULTI3-27HP230V1 (27K) - 11 COMBINATIONS

Two Units

Three Units

9K + 9K	9K + 12K	9K + 9K + 9K	9K + 12K + 12K*
9K + 9K	12K + 18K*	9K + 9K + 12K*	12K + 12K + 12K*
9K + 18K	18K + 18K*	9K + 9K + 18K*	

MULTI4-36HP230V1 (36K) - 27 COMBINATIONS

Two Units

Three Units

Four Units

9K + 18K	12K + 24K	9K + 9K + 9K	9K + 12K + 24K*	9K + 9K + 9K + 9K	12K + 12K + 12K + 12K*
9K + 24K	18K + 18K	9K + 9K + 12K	9K + 18K + 18K*	9K + 9K + 9K + 12K*	
12K + 18K	24K + 24K*	9K + 9K + 18K	12K + 12K + 12K	9K + 9K + 9K + 18K*	
12K + 18K	24K + 24K*	9K + 9K + 24K*	12K + 12K + 18K*	9K + 9K + 12K + 12K*	
		9K + 12K + 12K	12K + 12K + 24K*	9K + 9K + 12K + 18K*	
		9K + 12K + 18K*	12K + 18K + 18K*	9K + 12K + 12K + 12K*	

MULTI5-48HP230V1 (48K) - 28 COMBINATIONS

Two Units

Three Units

Four Units

Two Units

9K + 24K	18K + 24K	9K + 9K + 18K	12K + 12K + 12K	9K + 9K + 9K + 9K	12K + 12K + 12K + 18K*	9K + 9K + 9K + 9K + 9K
12K + 24K	24K + 24K	9K + 9K + 24K	12K + 12K + 18K	9K + 9K + 9K + 12K		9K + 9K + 9K + 9K + 12K
18K + 18K		9K + 12K + 12K	12K + 12K + 24K	9K + 9K + 9K + 18K		9K + 9K + 9K + 12K + 12K*
		9K + 12K + 18K	12K + 18K + 18K	9K + 9K + 12K + 12K		
		9K + 12K + 24K	18K + 18K + 18K*	9K + 9K + 12K + 18K		
		9K + 18K + 18K		9K + 12K + 12K + 12K		
				9K + 12K + 12K + 18K*		
				12K + 12K + 12K + 12K		

Note: It is critical to size the outdoor unit for the entire building load and each indoor unit for its individual zone load.

* If all indoor units (handlers) run simultaneously, their combined BTU output will not exceed the BTU rating of the outdoor unit (condenser).

NOTE: MULTI4-36HP230V1(36K) condenser combinations are not Energy Star certified.






MRCOOL[®]
COMFORT MADE SIMPLE

All **MRCOOL** Ductless Minisplits
HEAT and **COOL** efficiently and
can be programmed and controlled
remotely with our smartphone app*

Visit us at
mrcool.com

*Excluding Cassettes
and Ceiling Recessed.

Version Date 8-12-2021



 **MRCOOL[™]**
COMFORT MADE SIMPLE