



## OVERVIEW

Foil-Grip 1402 is a pressure-sensitive, 40-year cycle, duct joint and general purpose rolled mastic sealant. It provides an instant water-resistant air-tight grip to most surfaces including sheet metal, flex duct, and PVC-coated duct. Foil-Grip 1402 is suitable for subgrade application on PVC-coated duct and is ideal for replacement applications.

## PART NUMBERS

304093	1 Case w/ (24) 2" x 100' Rolls (Non-printed)
304094	1 Case w/ (16) 3" x 100' Rolls (Non-printed)
304095	1 Case w/ (12) 4" x 100' Rolls (Non-printed)
304096	1 Case w/ (8) 6" x 100' Rolls (Non-printed)
304083	1 Roll 36" x 100' (Non-printed)
304099	1 Case w/ (24) 2" x 100' Rolls (Printed)
304100	1 Case w/ (16) 3" x 100' Rolls (Printed)

## FEATURES AND BENEFITS

- Instant Adhesion
- Indoor/Outdoor
- True Zero VOC
- Metal & Subgrade PVC Ductwork
- All Pressure Classes Up To 20 inches W.C.
- 17-Mil Thickness

## SPECIFICATIONS/STANDARDS COMPLIANCE


Property	Method	Results
Color	Visual	Mil Finish Aluminum Printed/Non-Printed With Gray Butyl Sealant
Backing	Visual	2 mils Aluminum
Thickness	ASTM D3652	17 mils nominal
Peel Strength	ASTM D3330-83	>10 lbs/linear inch
Tensile Strength	ASTM D412	955 psi avg.
Elongation	ASTM D412	500%
Flexibility	ASTM C765	Excellent/No Cracking
Water Resistance	CSTM. RA 8.0	Pass
VOC	EPA Method # 2	0 g/l
Flame	ASTM E84/UL 723	20
Smoke	ASTM E84/UL 723	40
Service Temperature	ASTM D2485/D2243	-20°F to 200°F (-28.8°C to 93.3°C)
Pressure Test	Independent 24 Hour Test up to 5/8-inch Diameter	20 inch w.c.
Weather Resistance	ASTM G53	Passes 2,000 QUV
Bond Time		Immediate/Full Bond: 15 Minutes
UL Rating	UL 723	Passes/Classified
VOC Limitation	SCAQMD Rule 1168	Pass
NFPA	90A & 90B	Class 1

## STORAGE

Temperature	35°F to 110°F (1.7°C to 44°C) DO NOT FREEZE
Shelf Life	24 months
Flammability	Non-flammable

## APPLICATION

Temperature	35°F to 110°F (1.7°C to 44°C)
Preparation	Surface must be dry and free of dirt, oil and grease.
Method	Cut desired length, peel off release liner, apply. Removal or repositioning may damage Foil-Grip 1402 and surface. Overlap at ends. Use squeegee with heavy pressure to assure complete contact.
Clean Up	UN-TACK™ or Solvent (Use safe handling practices.)
Painting	Use paint appropriate for aluminum



## PRECAUTIONS

Surfaces must be clean and free of moisture and contamination. Do not apply this product in areas where temperatures will exceed 200°F. Keep out of the reach of children. DO NOT use where acidic or alkaline chemicals are present (ie., lab fume hood, vents, etc.).

**For Industrial Professional Use Only.**

## LEED

Post-industrial Recycled Content	0%
Pre-consumer Recycled Content	0%
VOC Content	0 g/L
Manufacturing Location(s)	Wylie, TX

