

Job Name:	
Tag#	



## Submittal Data Sheet

FFQ09Q2VJU / RX09RMVJU9A

.75-Ton Ceiling Mounted Heat Pump System



Complete warranty details available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com). To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. If product is installed in a commercial application, limited warranty period is 5 years.

### Indoor Specifications

Airflow Rate (cfm)	Cooling		Heating	
	H	M	H	M
	378	339	399	357
	L		L	
	268		282	
Sound (dBA) H / M / L	38 / 35 / 29		38 / 35 / 29	
Dimensions (H x W x D) (in)		10-1/4 x 22-5/8 x 22-5/8		
Weight (Lbs)		36		

### Outdoor Specifications

Compressor	Hermetically Sealed Swing Type			
Refrigerant	R-410A			
Factory Charge (Lbs)	2.09			
Refrigerant Oil	PVE (FVC50K)			
Airflow Rate (cfm)	Cooling		Heating	
	H	985	H	1,144
Sound Pressure Level (dBA)	46 / 50			
Dimensions (H x W x D) (in)	21-5/8 x 26-9/16 x 11-3/16			
Weight (Lbs)	63			

### Efficiency

Cooling		Heating	
SEER	20.90	HSPF	11.70
EER	13.0	COP	4.58

### Performance

Cooling (Btu/hr)	
Rated (Min/Max)	9,100 (4,600 / 11,100)
Sensible @ AHRI	7,990
Standard Operating Range	50°F – 115°F
Extended Operating Range*	-4°F – 115°F

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB  
Outdoor: 95°F DB/75°F WB

\*With field settings and wind baffle

Heating (Btu/hr)	
1: @ 47° Rated (Min/Max)	10,000 (4,600 / 14,000)
2: @ 17° Rated	6,000
3: @ 5°	4,480
Operating Range	5°F – 65°F

1: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 47°F DB/43°F WB  
2: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 17°F DB/15°F WB  
3: Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 5°F DB/5°F WB

### Electrical

	208/60/1	230/60/1
System MCA	9.0	9.0
System MFA	15	15
Compressor RLA	7.5	7.5
Outdoor fan motor FLA	.13	.13
Outdoor fan motor W	39	39
Indoor fan motor FLA	.28	.28
Indoor fan motor W	50	50

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)  
RLA: Rated load amps (A) W: Fan motor rated output (W)

### Piping

Liquid (in)	1/4
Gas (in)	3/8
Drain (in)	1-1/32
Max. Interunit Piping Length (ft)	65.625
Max. Interunit Height Difference (ft)	49.25
Chargeless (ft)	32.8
Additional Charge of Refrigerant (oz/ft)	.21

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: January 2022

Page 1 of 4


# FFQ09Q2VJU Dimensional Data



## • DECORATION PANEL


BYF060C2M1W	FRESH WHITE NO.5
BYF060C2M1S	DAIKIN SILVER

UNIT: inch(mm)




## A ARROW VIEW

NOTE 2.




## B ARROW VIEW

## • REQUIRED SPACE



## C ARROW VIEW



NOTE 1. STICKING LOCATION FOR MANUFACTURE'S LABEL

MANUFACTURE'S LABEL FOR DECORATION PANEL: ON THE INNER FRAME INSIDE SUCTION GRILLE

2. IN CASE OF USING WIRELESS REMOTE CONTROLLER, THIS POSITION WILL BE A SIGNAL RECEIVER

REFER TO THE DRAWING OF WIRELESS REMOTE CONTROLLER IN DETAIL

3. WHEN THE TEMPERATURE AND HUMIDITY IN THE CEILING EXCEED 86°F (30°C) AND RH 80% OR THE FRESH AIR IS INTRODUCED INTO THE CEILING OR THE UNIT CONTINUES 24 HOUR OPERATION, AN ADDITIONAL

4. INSULATION (THICKNESS 3/8 (10) OR MORE OF GLASSWOOL OR POLYETHYLENE FOAM) IS REQUIRED.

THOUGH THE INSTALLATION IS ACCEPTABLE UP TO MAXIMUM OF 23-7/16 (595) SQUARE CEILING OPENING.

KEEP THE CLEARANCE OF 3/8 (10) OR LESS BETWEEN THE MAIN UNIT AND THE CEILING OPENING SO THAT THE PANEL OVERLAP ALLOWANCE CAN BE ENSURED.

MODEL	AA	AB
FFQ09Q2VJU	1/4 (6.4)	3/8 (9.5)
FFQ12Q2VJU		1/2 (12.7)
FFQ15Q2VJU		
FFQ18Q2VJU		

3D106039


Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: January 2022

Page 2 of 4

# RX09RMVJU9 Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: January 2022

Page 3 of 4

## Optional Accessories



### Indoor Unit – One Controller & Decoration Panel are Required

Included	Part Number	Description
	BRC1E73	Wired Navigation Remote Controller
	BRC082A42W	Wireless Remote Controller (White)
	BRC082A42S	Wireless Remote Controller (Silver)
	DTST-ONE-ADA-A	Daikin <i>One+</i> Smart Thermostat
	BRC1H71W	<i>Madoka</i> Wired Controller
	BYFQ60C2W1S	Low Profile Decoration Panel (Silver) - $1\frac{13}{16} \times 24\frac{7}{16} \times 24\frac{7}{16}$
	BYFQ60C2W1W	Low Profile Decoration Panel (White) - $1\frac{13}{16} \times 24\frac{7}{16} \times 24\frac{7}{16}$
	BRYQ60A2S	Sensor kit (Silver) Intelligent Eye, Comfort Airflow, and Floor Sensor
	BRYQ60A2W	Sensor kit (White) Intelligent Eye, Comfort Airflow, and Floor Sensor
	BDBHQ44C60	Sealing member of air discharge outlet
	KAF441C60	Replacement Long Life Filter
	DACA-CP2-1	Maxi Orange Condensate Pump
	DACA-CP3-1	Mini Condensate Pump 5 gph
	AZAI6WSCDKA	DKN Cloud Wi-Fi Adaptor
	KRCSH2018-01	Button Sensor Kit
	AZAI6WSPDKC	DKN Plus Interface

### Outdoor Unit

Included	Part Number	Description
	DACA-WB-1	Powder-Coated Wall-Mounted Bracket
	KPW937F4	Low Ambient Wind Baffle /Air Adjustment Grille (09 & 12)
	KEH067A41EA	Drain Pan Heater
	KKG067A41	Back protection wire net (09 & 12)
	KPS067A41	Snow hood (intake side plate) (09 & 12)
	KPS067A42	Snow hood (intake rear place) (09 & 12)
	KPS067A44	Snow hood (outlet) (09 & 12)
	KKP937A4	Drain Plug for OD Unit

## Standard Equipment



Part Number	Description
6017766	Drain Pump
2139531	Float Switch

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: January 2022

Page 4 of 4