



Small Indirect Domestic Hot Water Tanks For Air-To-Water Heat Pumps, Geothermal HP, Boilers, Solar Water Heating, and Hydronic Systems

## DHW40 All-Stainless Steel w/ Duplex 2205 Inner Tank / 304 Outer Tank Enclosure

### Top Quality Indirect DHW Tanks

40 Gallons Gross / 34 Gallons Net  
 2205 Duplex Stainless Steel Inner Tank  
 316L Stainless Steel Indirect Coil  
 Indirect Coil: 1.25" x 33' Convolved (Wave)  
 304 Stainless Steel Outer Shell  
 2" Thick Polyurethane Insulation  
 1x Element Port, 1" NPSM, Up To 3500W  
 1x Drain Port 3/4" NPT Female  
 2x 1/2" Sensor Wells  
 1x Anode Port w/ Magnesium Anode  
 Pressure Drop @7 GPM 4.35 PSI / 10.04 Ft. Head  
 Pressure Rating 7 bar (100 psi)  
 Cold Inlet 1" NPT  
 Hot Outlet 1" NPT  
 1" NPT Coil Connectors  
 Tank Diameter 18.5"  
 Tank Height 57" + 3" Feet  
 Empty Tank Weight 80 Lbs.

Ultra-High Grade  
 Stainless Steel  
 Duplex 2205  
 Inner Tank



Convolved "Wave" Coil  
 For Faster Heating

16 Ft<sup>2</sup> Coil Face  
 .47 Ft<sup>2</sup> / Gallon

"Corner-Fit" Design  
 All Connections On Front

