



ICM2904

Intermittent Pilot Gas Ignition Control Module



Scan to see a full specifications, installation and agency certification information.

APPLICATIONS:

APPLIANCE | ELECTRICAL | HVAC/R | MARINE | POOL & SPA | RV



REPLACES

- Reznor: 257009

FEATURES

- ✓ Low cost, direct replacement ignition control
- ✓ Intermittent pilot gas ignition control module
- ✓ For use with intermittent pilot boilers, furnaces and other heating appliances
- ✓ Microprocessor-based
- ✓ Remote flame sensing
- ✓ Compatible with LP or natural gas
- ✓ Brown out monitoring circuit

SPECIFICATIONS

- Control voltage: 18-30 VAC
- Frequency: 50/60 Hz
- Pilot valve: 2A @ 24 VAC
- Main gas valve: 2A @ 24 VAC
- Current draw: 100mA maximum
- Pre-purge delay: 0 seconds
- Operating temperature: -40°F to 167°F (-40°C to 75°C)
- Humidity: 5%-95% R.H. (non-condensing) at +55°C

Content and specifications on sell sheets subject to change without notice.



7313 William Barry Blvd. North Syracuse, NY 13212
www.icmcontrols.com | 1-800-365-5525 | info@icmcontrols.com

LIS486