



ICM450A & ICM450A PLUS+

Programmable 3-Phase Line Voltage Monitors



Scan to see a full specifications, installation and agency certification information.

APPLICATIONS:

APPLIANCE

ELECTRICAL

HVAC/R

MARINE

POOL & SPA

RV

ICM450A



ICM450A PLUS+



Stop Motor Burnouts!

For more than two decades, ICM has been an innovator and a recognized leader in the manufacturer of line voltage controls designed to protect your most valuable equipment. The **ICM450A** and **ICM450A PLUS+** are the latest 3-phase offerings, providing superior motor protection from premature failure and damage caused by common voltage faults such as phase unbalance, over/under voltage, phase loss and phase reversal.

A design upgrade from our flagship **ICM450**, these newest models feature an easy to read, backlit display that makes quick work of adjusting the variable settings to better tailor the unit to the application. Common 1/4" spade terminations eliminate the potential for exposed wires and allow for a better and safer connection. Both models also include menu options for English and Spanish readouts.

Additionally, the **ICM450A PLUS+** offers a real time clock for date and time stamp of fault events when they occur along with a Modbus RS485 communications port for communicating with a standard building management system.

Both the **ICM450A** and **ICM450A PLUS+** are proudly manufactured in the USA by ICM Controls.

REPLACES

- **A-1:** EAC-800, EAC-8000, EAC-8002
- **Motorsaver:** 455
- **Wagner/DiversiTech:** DTP-3, WPC-800
- **Copeland:** 085-0160-00
- **SSAC:** QLM, QLV
- **Diversified:** AC-2020, AC-301, AC-302
- **Time Mark:** 265
- **Mars:** PFM-2000

FEATURES

	ICM450A	ICM450A PLUS+
✓ Backlit LCD	●	●
✓ Simultaneous 3-phase true RMS voltage monitoring	●	●
✓ Factory calibrated	●	●
✓ 3-phase voltages simultaneously displayed on LCD	●	●
✓ Fault memory	●	●
✓ Fault monitoring: High / low voltage, voltage unbalance, phase loss, phase reversal	●	●
✓ Real time clock, date and time stamped events		●
✓ Simple configuration	●	●
✓ Fully adjustable variables	●	●
✓ Modbus RS485 communications		●
✓ LED indicators	●	●
✓ Common 1/4" quick connect terminations	●	●
✓ English or Spanish menu options	●	●

SPECIFICATIONS

INPUT:

- **Voltage:** Universal, 190-600 VAC
- **Frequency:** 50-60 Hz
- **Load side monitoring:** Optional
- **Control voltage:** 18-240 VAC

OUTPUT:

- **Type:** Relay, SPDT
- **Voltage range:** 277 VAC @ 6A maximum

CONTROL OPERATING TEMPERATURE

- **Operating temperature:** -40°F to +149°F (-40°C to +65°C)
- **Storage temperature:** -40°F to +185°F (-40°C to +85°C)

MECHANICAL:

- **Mounting:** Surface mount using (2) #8 screws
- **Terminations:** 1/4" quick connects
- **Weight:** 12 ounces (341 grams)
- **ModBus:** RS485 Communication (**ICM450A plus+**)

ORDERING INFORMATION:

- **ICM450A:** Supersedes ICM450
- **ICM450A PLUS+:** Supersedes ICM450, ICM455

Content and specifications on sell sheets subject to change without notice.



7313 William Barry Blvd. North Syracuse, NY 13212
www.icmcontrols.com | 1-800-365-5525 | info@icmcontrols.com

LIS445