



### APPLICATIONS:

APPLIANCE

ELECTRICAL

HVAC/R

MARINE

POOL & SPA

RV



### REPLACES

- Wagner/DiversiTech: DSP-1

### FEATURES

- ✓ Protects against over and under voltage, and rapid short cycling caused by transient faults and power interruptions
- ✓ Easy-view, backlit digital display
- ✓ Adjustable voltage set point
- ✓ Adjustable anti-short cycle time delay
- ✓ Adjustable response time
- ✓ Control mode (optional)
- ✓ 5-fault memory
- ✓ Universal line voltage input
- ✓ Heavy duty SPDT relay output
- ✓ Universal control voltage input (for integrating a thermostat)

### OVERVIEW

The **ICM492** continuously monitors incoming line voltage for faults and displays RMS voltage on the digital display. When line voltage is appropriate, the **ICM492** will close COM and N.O. relay contacts. When incoming line voltage is outside of the user selected parameters, the **ICM492** will close COM and N.C. relay contacts and indicate a fault condition by flashing **FAULT** on display. The **SELECT** menu has the following user adjustable settings: voltage set point, time delay, over voltage, under voltage, control mode, and response time. Time delay prevents system short cycling caused by transient faults and rapid power interruptions. The response time on the fault condition can be adjusted to help reduce nuisance trips from transient faults. When Control Mode setting is selected ON, the **ICM492** will close COM and N.O. relay contacts only when control voltage is present at Control Voltage terminals. The relay contacts can be used to direct drive the load as long as current rating is not exceeded.

### SPECIFICATIONS

#### USER ADJUSTABLE SETTINGS:

- **Voltage set point:** 95-280 VAC
- **Anti-short cycle time delay:** 0-720 seconds
- **Over voltage setting:** 5-25%
- **Under voltage setting:** 5-25%
- **Control mode:** On and Off
- **Response time:** 0.1 to 10 seconds

#### INPUTS:

- **Voltage:** 80-300 VAC
- **Frequency:** 50/60 Hz
- **Accuracy:**  $\pm 2\%$
- **Low power consumption:** Maximum 50 mA @ 120V, maximum 100 mA @ 240V
- **Control voltage:** 24 to 240 VAC

#### OUTPUT

- **Type:** dry relay contacts
- **Form:** SPDT
- **Relay contact ratings:**
  - **N.C. contacts:** 10A resistive @ 277 VAC
  - **N.O. contacts:** 10A resistive @ 277 VAC
  - **Connection terminals:** 0.25" male fast-on