



APPLICATIONS:

APPLIANCE | ELECTRICAL | HVAC/R | MARINE | POOL & SPA | RV



UL US
LISTED
E492643
CLOCK OPERATED SWITCH

Control only without enclosure: Order ICM550

OVERVIEW

When mode B is selected and the unit is in the timed cycle (clock dip switches in the on position), the load will be turned on with the back up source. At the end of the timed cycle, the unit will return to normal operation until the next preset interval occurs.

If Mode A is selected, the load will be off during the timed cycle and the back up source will be on. At the end of the timed cycle, the unit will return to normal operation until the next preset interval occurs.

REPLACES

- **Intermatic/Grasslin:** 010-0011B, DT040, DT140, DTAV40, DTAV40M, DT-B, DTMV, DTSX
- **Paragon:** 8041, 8045, 8047, 8141, 8143, 8145, 8245, 8247
- **Precision:** 6041, 6045, 6047, 6141, 6145

FEATURES

- ✓ Timed or manual termination
- ✓ Adjustable 15 minutes to 23 hours 45 minutes defrost cycle
- ✓ High power relay outputs
- ✓ 100% monitoring of inputs and outputs
- ✓ Simple to use, drag & drop replacement for popular models
- ✓ User-friendly time clock
- ✓ Rugged, NEMA/TYPE 4X rated plastic, weatherproof enclosure
- ✓ Easy to mount and lockable
- ✓ Helps to protect controls from harsh environmental conditions such as temperature, shock, humidity and vibration
- ✓ Control only without enclosure: **(Order: ICM550)**
- ✓ *Enclosure not sold separately*

SPECIFICATIONS

ELECTRICAL RATING

- **Voltage:** 120-240 VAC
- **Frequency:** 60 Hz

OUTPUT

- **Type:** Relay
- **Form:** SPDT, SPST
- **Rating:**
 - [2] & [4]: 30A R, 1HP @ 120 VAC, 2HP @ 240 VAC
 - [1] & [3]: 40A R, 1HP @ 120 VAC, 2HP @ 240 VAC
 - [1] & [F]: 30A R, 1HP @ 120 VAC, 2HP @ 240 VAC

TIMING

- **Minimum cycle time:** 15 minutes
- **Maximum cycle time:** 23 hours 45 minutes
- **Terminate cycle:** Cycle can be terminated by shorting "X to N"

STATUS LED

- **Cycle mode:** (Red LED)
- **Normal mode:** (Green LED)