

SWITCH / DEVICE SELECTOR

Mechanical

| DEVICE | PATENT | APPLICATION | | | | | | | | DMSS |
|-------------------------------------|-----------------------------------|--------------------------|------------------------------------------------------------|-------------------------------------------|-----------------------------------------------------------------------|---------------------------------------------------------------------------|--------------------------|-------------------------------------------|---------------------------------|------|
| | | PRIMARY DRAIN LINES ONLY | PRIMARY DRAIN LINE OR PRIMARY DRAIN PAN (AUXILIARY OUTLET) | PRIMARY DRAIN PAN (AUXILIARY OUTLET) ONLY | PRIMARY DRAIN PAN (AUXILIARY OUTLET) & SECONDARY DRAIN PAN (2 PROBES) | PRIMARY DRAIN LINE (OR AUXILIARY OUTLET) & SECONDARY DRAIN PAN (2 PROBES) | SECONDARY DRAIN PAN ONLY | PRIMARY & SECONDARY DRAIN PANS (2 PROBES) | PRIMARY OR SECONDARY DRAIN PANS | |
| SS1 [†] | 10,406,570 | ✓ | | | | | | | | |
| SS1P ^{†*} | 10,406,570 | ✓ | | | | | | | | |
| SS2 | | | | ✓ | | | | | | |
| SS2P [†] | | | | ✓ | | | | | | |
| SS3 | 6,698,215 | | | | | | | | ✓ | |
| SS3P [†] | 6,698,215 | | | | | | | | ✓ | |
| EZT205 (contains trap) | | ✓ | | | | | | | | |
| EZT210 (contains trap) | | ✓ | | | | | | | | |
| EZT224 | | | | ✓ | | | | | | |
| EZT225 | | | ✓ | | | | | | | |
| EZT226 | | | | ✓ | | | | | | |
| EZT230 (contains trap) | | ✓ | | | | | | | | |
| AG1100+ (metal only) | 7,710,283 | | | | | | ✓ | | | |
| AG1200+ | 7,710,283 | | | | | | ✓ | | | |
| AG4200M [†] (drain outlet) | 7,710,283 • 7,878,019 • 8,317,169 | | | | | | ✓ | | | |

Electronic

| | | | | | | | | | | |
|-------------------------------------|-----------------------------------------------|--|--|--|---|---|---|---|---|---|
| AG1250E | 8,578,770 | | | | | | ✓ | | | |
| AG3150E [†] | 8,151,580 • 8,561,417 • 8,578,770 • 7,774,395 | | | | ✓ | | | | | |
| AG3175E ^{†*} | 8,151,580 • 8,561,417 • 8,578,770 • 7,774,395 | | | | ✓ | | | | | |
| AG3180E ^{†*} | 8,578,770 • 7,744,395 | | | | | | | ✓ | | |
| AG4200E [†] (drain outlet) | 8,578,770 • 8,317,169 | | | | | | ✓ | | | |
| SS103E [†] | | | | | ✓ | ✓ | | | | |
| SS500EP [†] | Patent Pending | | | | | | | | ✓ | |
| SS610E | 8,887,392 | | | | | | | | | ✓ |
| SSW | Patent Pending | | | | | | ✓ | | | |

Cleanout

| | | | | | | | | | | |
|-----|------------|---|--|--|--|--|--|--|--|--|
| SC1 | 10,406,570 | ✓ | | | | | | | | |
|-----|------------|---|--|--|--|--|--|--|--|--|

[†] Also a cleanout device
[°] Plenum rated

[^] RectorSeal Goliath, Titan & Spartan drain pans only
^{*} Able to handle 2 probes

SWITCH / DEVICE FEATURES

Mechanical

| DEVICE | SENSOR TYPE | SWITCH TYPE | | SENSING TECHNOLOGY | | SUPPLY VOLTAGE | SWITCHING VOLTAGE | SWITCHING CURRENT | | | SWITCHING LOGIC | | |
|---------|-------------|-------------|-------------|--------------------|----------|----------------|-------------------|----------------------------------------------------------------------------|-----------|-----------|----------------------|-------------------------|---------|
| | FLOAT | REED | MICROSWITCH | BUOYANCY / MAGNET | BUOYANCY | NOT NEEDED | 0-24V | 0 – 1.25 AMP (carry current, UL rating) 0 – 0.5 AMP (switching current) | 0 – 4 AMP | 0 – 5 AMP | NORMALLY CLOSED (NC) | NC ONLY w/NO Capability | NC / NO |
| SS1 | ✓ | ✓ | | ✓ | | ✓ | ✓ | ✓ | | | ✓ | | |
| SS1P | ✓ | ✓ | | ✓ | | ✓ | ✓ | ✓ | | | ✓ | | |
| SS2 | ✓ | ✓ | | ✓ | | ✓ | ✓ | ✓ | | | ✓ | | |
| SS2P | ✓ | ✓ | | ✓ | | ✓ | ✓ | ✓ | | | ✓ | | |
| SS3 | ✓ | ✓ | | ✓ | | ✓ | ✓ | ✓ | | | ✓ | | |
| SS3P | ✓ | ✓ | | ✓ | | ✓ | ✓ | ✓ | | | ✓ | | |
| EZT205 | ✓ | | ✓ | | ✓ | ✓ | ✓ | | ✓ | | | ✓ | |
| EZT210 | ✓ | | ✓ | | ✓ | ✓ | ✓ | | ✓ | | | ✓ | |
| EZT224 | ✓ | | ✓ | | ✓ | ✓ | ✓ | | ✓ | | | ✓ | |
| EZT225 | ✓ | | ✓ | | ✓ | ✓ | ✓ | | ✓ | | | ✓ | |
| EZT226 | ✓ | | ✓ | | ✓ | ✓ | ✓ | | ✓ | | | ✓ | |
| EZT230 | ✓ | | ✓ | | ✓ | ✓ | ✓ | | ✓ | | | ✓ | |
| AG1100 | ✓ | | ✓ | ✓ | | ✓ | ✓ | | | ✓ | | | ✓ |
| AG1200 | ✓ | | ✓ | ✓ | | ✓ | ✓ | | | ✓ | | | ✓ |
| AG4200M | ✓ | | ✓ | ✓ | | ✓ | ✓ | | | ✓ | | | ✓ |

Electronic

| DEVICE | SENSOR TYPE | SWITCH TYPE | SENSING TECHNOLOGY | SUPPLY VOLTAGE | | SWITCHING VOLTAGE | | SWITCHING CURRENT | SWITCHING LOGIC |
|---------|------------------|-------------|--------------------|----------------|--------------|-------------------|----------|-------------------|-----------------|
| | METAL PINS/PROBE | RELAY | WATER RESISTANCE | 24VAC | 110 – 230VAC | 0 – 24V | 0 – 250V | 0 – 5 AMP | NC / NO |
| AG1250E | ✓ | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ |
| AG3150E | ✓ | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ |
| AG3175E | ✓ | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ |
| AG3180E | ✓ | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ |
| AG4200E | ✓ | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ |
| SS103E | ✓ | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ |
| SS500EP | ✓ | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ |
| SS610E | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ | ✓ |
| SSW | ✓ | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ |