

# Window Units - Remote with Electric Heat

1 yr

## FEATURES

- Multiple Functions - Cooling, Dehumidifying & Fan Ventilation
- Installation Kit with Expandable Side Panels
- Retracting Louvers



## Electrical Requirements



NEMA 5-15A  
115 VOLT  
15 AMP



NEMA 6 - 15P  
230 VOLT  
15 AMP



NEMA 6 - 20P  
230 VOLT  
20 AMP



NEMA 6 - 30P  
230 VOLT  
25 AMP



NEW

	While Supplies Last	Replaces WH48YRB			
Model Number	WH48YRB	WH48YRC	WH412ZRB	WH418ZRC	WH425ZRC
Product Code	422-0115	422-0134	422-0116	422-0129	422-0130
BTU Cooling	8,000	8,000	11,600 / 12,000	18,200 / 18,500	24,700/25,000
BTU Heating	3,500	3,500	8,500/11,000	13,000 / 16,000	13,000/16,300
EER	10.9	10.9	10.9	10.7	9.4
Dehumidification (pints/hour)	1.6	1.6	2.5	3.8	6.3
Airflow (CFM)	593 / 520 / 441	642 / 563 / 482	696 / 633 / 553	446/388/329	523/485/445
Voltage	115	115	208 / 230	208 / 230	208 / 230
Frequency / Cycle	60 HZ	60 HZ	60 HZ	60 HZ	60 HZ
Amps Cooling	6.3	6.4	5.2 / 5.0	8.3 / 7.7	12.4 / 11.3
Amps Heating	11.6	11.7	14.5/16		
Watts Cooling	734	734	1064 / 1100	1701/1729	2628/2660
Watts Heating	1220	1220	2821/3450	4160/5060	4200/5100
Plug Type / Nema #	5-15A	5-15P	6-20P	6-30P	6-30P
Power Cord Rating/ amps	15	15	20	30	30
Power Cord Type	LCDI	LCDI	LCDI	LCDI	LCDI
Power Cord Length	76	96	69	78	84
Refrigerant	R410A	R410A	R410A	R410A	R410A
Refrigerant Charge/ Oz.	13.4	13.4	22.22	28.92	34.22
Sound (Indoor/Outdoor) dba	57.5 / 64.5	57.2 / 64.3	60.9 / 67.2	60/66	63.2/68.2
4 Way Air Adjustment	Yes	Yes	Yes	YES	YES
2 Way Air Swing	Yes	Yes	Yes	YES	YES
Air Discharge	Top Front	Top Front	Top Front	Top Front	Top Front
Motor Type	Ball bearing	Ball bearing	Ball bearing	Ball Bearing	Ball Bearing
Motor Capacitor / mfd	50 + 15μF(Dual Type)	45 + 15μF(Dual Type)	4μF	8μF	8μF
Controls	Remote	Remote	Remote	Remote	Remote
Operating Range	64 - 109 °F	64 - 109 °F	64 - 109 °F	64 - 109 °F	64 - 109 °F
Cabinet Size/ inches					
Width	22.6"	22.6"	22.6"	23.6"	26.5"
Depth	23"	23"	23"	25.4"	26.5"
Height	16.1"	16.1"	16.1"	17.9"	18.6"
Window Opening Width (min / max)	26.8" - 36"	26.8" - 36"	26.8" - 36"	26.5 - 40.5"	31 - 42"
Thru. Wall Max. Thickness (Inches)	6.1"	6.1"	6.1"	8"	10"
N.W. / G.W lbs.	70.6 / 82	75.8 / 87.3	83.8 / 94.8	118.4/133.4	136.5/155.6
Approvals	cULus	cULus	cULus	cULus	cULus
Chassis Slide Out	Yes	Yes	Yes	Yes	Yes