

Window Units

Heat Pump with Remote

FEATURES

- Multiple Functions - Cooling, Dehumidifying & Fan Ventilation
- Installation Kit with Expandable Side Panels
- Retracting Louvers



Electrical Requirements



NEMA 5-15A
115 VOLT
15 AMP



NEMA 6 - 15P
230 VOLT
15 AMP



NEMA 6 - 20P
230 VOLT
20 AMP



NEMA 6 - 30P
230 VOLT
25 AMP



Window
Units



Model Number	WHP412ZRB	WHP418ZRB
Product Code	422-0119	422-0120
Rated Voltage (VAC)	208 / 230	208 / 230
Cooling Capacity	10,600 / 11,000	17,400 / 17,700
Heating Capacity	9,600 / 10,000	15,700 / 16000
Electric Heat Capacity	8,500 / 11,000	9,100 / 11,200
EER Rating	9.8	9.8
COP Rating	9.2	9.2
Dehumidification (pints/hr)	2.5	3.8
Air Flow Max (CFM)	696 / 633 / 553	523 / 485 / 445
Operating Voltage Range (VAC)	198 - 253	198 - 253
Frequency/Cycle	60	60
Cooling Amps	5.2 / 5.0	8.65 / 8.05
Cooling Watts	1082 / 1122	1775 / 1805
Heating Amps	5.0 / 4.8	7.45 / 7.05
Heating Watts	1043 / 1087	1530 / 1600
Electric Heat Amps	14.5 / 16	14.5 / 16
Electric Heat Watts	2821 / 3450	2821 / 3450
Plug Type - LCDI	6-20P	6-20P
Power Cord Rating (amps)	20	20
Power Cord Length (Inches)	69"	5.9
Minimum Circuit Breaker Size (amps)	20A	20A
Minimum Circuit Capacity (amps)	20A	20A
Refrigerant Charge - R410a (oz.)	29.63	35.3
Max dbA Level (Indoor/Outdoor)	60.9 / 67.2	63.2 / 68.2
4 Way Air Adjustment	Yes	YES
2 Way Air Swing	Yes	YES
Air Discharge	Top Front	Top Front
Motor Type	Ball bearing	Ball bearing
Fan Motor Capacitor (MFD)	4μF	8μF
Controls	Remote	Remote
Ambient Operating Temperature	64 - 109 °F	64 - 109 °F
Unit Size (Inches)		
Width	22.6"	26.5"
Depth	23"	26.5"
Height	16.1"	18.6"
Window Width Opening (Inches)	26.8" - 36"	31 - 42"
Thru. Wall Max. Thickness (Inches)	6.1"	10"
Weight Gross/Net. (Lbs)	90 / 97	127 / 142
Certification	cULus	cULus
Chassis Slide Out	Yes	Yes