



Flaretite - Refrigeration & Gas Seals

The ultimate solution for eliminating leaks!



SLASH THE COSTS OF SERVICING, DOWNTIME & CALL BACKS.

COMPATIBLE WITH ALL COMMON REFRIGERANTS INCLUDING POE & PVE OILS



- For common aluminum and brass fittings.
- SAE (US Standard) 45° flare seals for inch tubing sizes.
- Stamped copper seal with standard Loctite Vibra seal coating.
- Rated for -40°F to 300°F temperature & all common gases & fluids.
- 5 sizes & 21 combinations: 1/4" • 3/8" • 1/2" • 5/8" • 3/4"

**GREAT FOR INSTALLING MINI-SPLIT
& VRF SYSTEMS**

Code	Description	Qty.
97210	Combo Kit - 9 seals each of sizes 1/4", 3/8", 1/2", 5/8" (36 seals total)	6 kits/case
97211	Combo Kit - (2) 3/8", (2) 3/4"	10 kits/case
97212	Combo Kit - (2) 3/8", (2) 5/8"	10 kits/case
97213	Combo Kit - (2) 3/8", (2) 1/2"	10 kits/case
97214	Combo Kit - (2) 1/4", (2) 5/8"	10 kits/case
97215	Combo Kit - (2) 1/4", (2) 1/2"	10 kits/case
97216	Combo Kit - (2) 1/4", (2) 3/8"	10 kits/case
97217	(10) 3/4" Seal Kit	10 kits/case
97218	(10) 5/8" Seal Kit	10 kits/case
97219	(10) 1/2" Seal Kit	10 kits/case
97220	(10) 3/8" Seal Kit	10 kits/case
97221	(10) 1/4" Seal Kit	10 kits/case
97222	(200) 5/8" Seal Kit	4 kits/case
97223	(200) 1/2" Seal Kit	4 kits/case
97224	(200) 3/8" Seal Kit	4 kits/case
97225	(200) 1/4" Seal Kit	4 kits/case
97226	(100) 3/4" Seal Kit	4 kits/case
97227	(100) 5/8" Seal Kit	4 kits/case
97228	(100) 1/2" Seal Kit	4 kits/case
97229	(100) 3/8" Seal Kit	4 kits/case
97230	(100) 1/4" Seal Kit	4 kits/case

FEATURES

- 45° Copper Stamping with Loctite coating
- Locking tabs clip seal securely on fitting
- Conical rings for multiple points of contact
- Made for all common 45° fittings
- Rated for -40°F to 300°F
- Pressure rated up to 10,000 psi

APPLICATION • Used to prevent leaks that are caused by galling, vibration, pulsation & extreme temp changes • A perfect solution for a leak free connection in today's harshest environments

RECOMMENDED FOR

- Service & repair
- Mini-Split & VRF installations
- Commercial chillers & coolers
- Marine & aviation refrigeration



Manufacturer's Torque Specifications (ft-lbs)

	1/4"	3/8"	1/2"	5/8"	3/4"
Daikin	10.4 - 12.7	24.1 - 29.4	36.5 - 44.5	45.6 - 55.6	71.7 - 87.5
LG	13.9 - 18	24.5 - 30.3	39.7 - 47.7	45.5 - 59.2	71.61 - 87.52
Fujitsu	11.8 - 13.3	23.6 - 31	36.1 - 45	46.5 - 55.3	66.4 - 81.1
Mitsubishi	10 - 13.1	25 - 30	36 - 42	54 - 58	-
Gree	10 - 13.1	25 - 30	36 - 45	50 - 60	-

Flaretite Recommended Torque Specifications (CU-SPP)

1/4"	3/8"	1/2"	5/8"	3/4"
14 - 18 ft-lbs	24 - 30 ft-lbs	40 - 47 ft-lbs	46 - 59 ft-lbs	72 - 86 ft-lbs

RectorSeal, LLC 2601 Spenwick Drive - Houston, TX 77055 800-231-3345 rectorseal.com
 PO Box 3119 Clontarf DC, QLD 4019, Australia 07-3267-7277 rectorseal.com.au

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice.

©2019 RectorSeal. All rights reserved. R50391-0519 Flaretite is a registered trademark of Flaretite, Inc. Corp.