



A CSW Industrials Company

PRODUCT DATA SHEET

ARMORPAD™ FOAMCORE Equipment Pad

Description

ArmorPad™ Foamcore is a high-strength and light-weight equipment pad that provides support and lift for the outdoor unit. It is constructed of a dense foam core base enveloped in a shell of durable polymer on five sides that aesthetically simulates the texture and color of gray concrete. The entire product line of 24, 30, 32, 36, and 40-inch-square (61, 76, 81, 91, 101-cm) x 3-inch-high (7.6-cm) models needs only one person to transport and install.

The ArmorPad Foamcore's polymer shell is molded into a one-piece, strong and durable extrusion that's compliant with ASTM D-2299 standard. The polymer surface perpetuates a brand new appearance, because of its built-in resistance to UV degradation, coil cleaning chemicals, landscaping chemicals, weather and urine. The foam core bottom features a unique foil-backing that resists moisture and contains an EPA registered insecticide built-in to protect the product.



Applications

Recommended for residential and commercial HVAC units, ArmorPad Foamcore provides support and lift for the HVAC condenser unit outdoor. It provides a strong and stable equipment platform for uneven surfaces.

Packaging

Code	Foamcore Size	Qty per Pallet	Lbs per Pallet	Cubic Feet
84404	32"x 32"x 3"	14	86.1	28.12
84405	36"x 36"x 3"	14	106.4	35.46
84406	40"x 40"x 3"	14	134.32	43.66
84407	24"x 24"x 3"	28	98	31.63
84408	30"x 30"x 3"	28	151.2	49.12

Characteristics | Features

- Light-weight at less than 11 lbs
- Extreme durability with load capacity of more than 1400 lbs
- High anchoring strength for securing equipment
- Solid-fill interior
- Textured surface to prevent equipment sliding
- Long-term exterior weather resistance including UV resistance, and freeze and thaw resistance
- Vibration absorbing
- Chemical resistance against R-407c and R-410A, compressor oil, coil cleaners, and salt solution
- Contains an EPA registered insecticide built-in to protect the product
- Does not chip and is not damaged by weed trimmers

LIMITED WARRANTY

RectorSeal, LLC (“RectorSeal”) warrants the following:

1. LIMITED WARRANTY

The Product subject to this sale will be of good quality and workmanship and conform to the Product’s performance specifications. If during the Warranty Period, the purchaser believes that a Product covered under this Limited Warranty fails to conform to specifications or is defective by reason of faulty design, workmanship or materials, then the purchaser must promptly notify RectorSeal within 15 days of such determination (a “Defect Notice”). RectorSeal will then inspect the Product and determine, in its reasonable judgment, whether an adjustment, repair, or replacement of the Product is warranted, and if so, promptly make the adjustment, repair, or replacement at no additional charge to the purchaser.

RectorSeal may elect to repair the Product on site or have the Product returned to RectorSeal’s premises. If the Product is returned to RectorSeal, risk of loss to the Product will at all times remain with the purchaser, and shipping costs will be borne by RectorSeal where the Product defect is covered by this Limited Warranty.

The foregoing Limited Warranty will be voided in the following conditions:

- I. The Product has not been used or stored (with proper documentation) in a manner consisted with the operating and maintenance instructions of RectorSeal or in compliance with the use or proper purpose intended by RectorSeal;
- II. The installation or application of the Product has not been performed in accordance with RectorSeal’s instructions.
- III. The Product defect has been caused by fire, accident, abuse, misuse (i.e. the Product’s sealed motor housing has been opened), unauthorized alteration, repair, reconstruction or maintenance (including modification of labels or packaging) or the use of sub-standard consumables (ordinary wear and tear excepted);
- IV. The Product defect has arisen from a design, specification, component or material supplied by or on behalf of the purchaser or a third party; or
- V. The Product or any part of the Product has been used or combined with goods, products, hardware or other materials, or has been replaced with a part not supplied or approved by RectorSeal.

2. LIMITED WARRANTY TERM

The duration of this Limited Warranty is 12 months from the Product’s date of sale (the “Warranty Period”).

3. LIMITATION OF LIABILITY AND DISCLAIMER

Before using the Product, the purchaser is solely responsible for determining the suitability of the Product for the intended use, and the purchaser assumes all risk and liability whatsoever in connection therewith. The terms set forth herein are the purchaser’s exclusive remedy for breach of this Limited Warranty. RectorSeal does not warrant any products or services not provided by RectorSeal, or any third-party products or services that incorporate the Products. **RectorSeal will not under any circumstances be liable for any consequential, incidental, special or punitive damages or losses, whether direct or indirect.**

EXCEPT FOR THE LIMITED WARRANTY SET FORTH HEREIN, RECTORSEAL MAKES NO WARRANTY WHATSOEVER WITH RESPECT TO THE PRODUCT, INCLUDING (A) WARRANTY OF MERCHANTABILITY; OR (B) WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, WHETHER EXPRESS OR IMPLIED, BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com
3255 Wyandotte St. East, Windsor, ON N8Y 1E9, 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor’s and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2021 RectorSeal. All rights reserved. R50142-03/21