




Submittal Data Sheet

Washable Filter

ALFH1620E, ALFH2023E, ALFH1912201E



DESCRIPTION

Aluminum framed filter with synthetic hog hair is ideal for applications needing high dust holding arrestance and low resistance.

FEATURES

- Constructed of a one piece all aluminum frame with mitered corners
- Washable synthetic media made from extra heavy weight polyester fibers and boned into a tough, durable air filter
- Retaining expanded aluminum grid are on both air entry and exit side for extra strength and support

SPECIFICATIONS

Model No.:	ALFH16201E	ALFH20231E	ALFH1912201E
Unit Compatibility:	FXTQ09TAVJUA, FXTQ12TAVJUA, FXTQ18TAVJUA, FXTQ24TAVJUA, FXTQ30TAVJUA, FXTQ36TAVJUA FTQ18TAVJUA, FTQ24TAVJUA, FTQ30TAVJUA, FTQ36TAVJUA	ARUF37D14, ARUF43D14, ARUF47D14, ARUF49D14, ARUF61D14, ASPT47D14, ASPT49D14, DV42PTCD14, DV60PTCD14 FXTQ54TAVJUA, FXTQ60TAVJUA	ARUF37C14, ARUF43C14, ARUF49C14, ASPT47C14, ASPT59C14, DV36PTCC14, DV36PVCD14, DV48PTCC14, DV48PTCD14 FXTQ42TAVJUA, FXTQ48TAVJUA FTQ42TAVJUA, FTQ48TAVJUA
Shipping Weight	1.20 lb. (0.54kg)	1.60 lb. (0.73kg)	1.40 lb. (0.64kg)
Dimensions (W x H x D):	16" x 20" x 1" (406mm x 508mm x 25mm)	20" x 23" x 1" (508mm x 584mm x 25mm)	19.5" x 20" x 1" (495mm x 508mm x 25mm)
Filter Rating:	55-60% Arrestance		
Filter Type:	Washable		
Initial/ Final Pressure Loss:	0.09" / 1.0"		

Daikin North America LLC, 5151 San Felipe, Suite 500, Houston TX, 77056

www.daikinac.com www.daikincomfort.com

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations).