



A CSW Industrials Company

PRODUCT DATA SHEET

SURGEMASTER™

Boiler Surge Inhibitor

Description

Surgemaster coagulates/precipitates organic impurities like algae, cutting oil, & the protective coating manufacturers place in new boilers. The corrosion inhibitor dissolves gases & prevents the formation of corrosive acids which pit metal and cause rust.

Applications

Surgemaster is especially effective in curing boiler problems (cutting oils and protective coatings) associated with new installations. Sure-cure color indicator tints boiler water to take the guesswork out of treatment dosage



Instructions for Use

READ ALL DIRECTIONS, SDS AND LABEL BEFORE USING

Steam Boiler (1) Completely drain the boiler to flush previously installed chemicals, and refill boiler. (2) Shake container to aerate powder. Sift powder into boiler or mix powder with 1/2 gallon of water and pour into system. (3) Refill boiler to slightly above water level and steam for 15 minutes. (4) Yellow-green water in the gauge indicates the treatment is sufficient. Pinkish-red colored water indicates a second container of Surgemaster must be added. (5) Surgemaster remains in the system to inhibit surging and corrosion.

New Boiler - To prevent surging due to protective coating in new boilers, add Surgemaster on installation. Note: Contains no petroleum distillates - safe for systems.

For additional technical information, call Toll Free 1-800-231-3345

Characteristics | Features

- Inhibits corrosion
- Produces clean, dry steam
- Contains no petroleum distillates
- Sure-cure color indicator

Packaging

| Code | Size | Qty. per Case | Lbs. per Case | Cubic Ft per Case |
|-------|----------------|---------------|---------------|-------------------|
| 68742 | 5.3 oz (150 g) | 12 | 7 | 0.46 |

Specifications

| | |
|---------------------|-----------------------|
| Flash Point SETA CC | None |
| Color | Greenish white powder |
| Shelf Life | 2 years |

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances



DANGER!

May cause cancer by inhalation.
Causes damage to lungs through prolonged or repeated exposure via inhalation.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300.

Contains: Diatomaceous Earth 91053-39-3, Monosodium Phosphate 7558-80-7, Sodium Sulfite 7757-83-7, Crystalline Silica 14808-60-7, Dimethyl Siloxane 67762-90-7

Precautionary Statements: PREVENTION: Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not eat, drink or smoke when using this product. Wear protective gloves and safety glasses or goggles. In case of inadequate ventilation wear respiratory protection.

RESPONSE: If exposed or concerned: Get medical advice.

DISPOSAL: Dispose of contents/container to an approved waste disposal plant.

KEEP OUT OF REACH OF CHILDREN.

For additional information, refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345.



WARNING: This product can expose you to Crystalline Silica, which is known to the State of California to cause cancer. For more information go to: www.P65Warnings.ca.gov.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50490-0820